

→ Local extensions

- For XT 20 only (1 local extension per module)
- Millenium - Millenium local link
- Doubles the hardware and software capacities
- Transparent communication between two XT 20 units
- Max. distance between two XT 20 units : 10 metres
- Cable type : screened twisted pair



Specifications

| Type | Designation | Supply | Code |
|-------|---------------------------------|----------------|------------|
| XL 01 | M2 - M2 local link (2 modules) | universal | 88 950 200 |
| XL 05 | 4 solid state outputs | universal | 88 950 204 |
| XL 06 | 2 Relay outputs (250mA Maximum) | 100 → 240 V AC | 88 950 810 |

→ Adjacent extensions

- For XT 20 only (one adjacent extension per module)
- 4 or 6 additional inputs/outputs




Specifications

| Type | Designation | Supply | Code |
|-------|------------------------------|----------------|------------|
| XC 01 | 4 inputs PNP 2 relay outputs | 24 V DC | 88 950 210 |
| | 4 inputs relay outputs | 24 V AC | 88 950 211 |
| | 4 inputs 2 relay outputs | 100 - 240 V AC | 88 950 212 |
| | 4 inputs 2 relay outputs | 12 V DC | 88 950 215 |
| | 4 inputs NPN 2 relay outputs | 24 V DC | 88 950 219 |

Dimensions

XC 01



→ Communication modules

- For XT 20 only (one adjacent extension per module)
- Communication using MODBUS or AS-i protocol (Slave module)




Specifications

| Type | Designation | Supply | Code |
|--------|-------------------------------------|---------|------------|
| XC 02 | AS-i communication module 24 V DC | 24 V DC | 88 950 213 |
| XC 03 | MODBUS communication module 24 V DC | 24 V DC | 88 950 214 |
| Modems | STN | | 88 950 106 |
| | GSM | | 88 950 107 |

Dimensions

XC02/XC03



Modem

