

1520230 -9 Product Details

No Image Available

1520230 -9

 [Active](#)

Power Toggle Switches

[Not Reviewed for ELV/RoHS Compliance](#)

Product Highlights:

- ? Double Pole - Single Throw Configuration (Pole - Throw)
- ? Toggle Length = 20.62 mm
- ? Toggle Style = Baton
- ? Bushing Length = 11.91 mm
- ? Termination Type = Screw -In Terminal

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [Customer Drawing](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Configuration (Pole - Throw) = Double Pole - Single Throw
- ? Termination Type = Screw -In Terminal

Electrical Characteristics:

- ? UL/CSA 250V Current Rating (Amps.) = 20
- ? UL/CSA 125V Horse Power Rating (hp) = 1.50
- ? UL/CSA 250V Horse Power Rating (hp) = 2.00

Housing Related Features:

- ? Toggle Length (mm [in]) = 20.62 [0.812]
- ? Toggle Style = Baton

Configuration Related Features:

- ? Bushing Length (mm [in]) = 11.91 [0.469]

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not reviewed for ELV/RoHS compliance
- ? [Lead Free Solder Processes](#) = Not reviewed for lead free solder process

Other:

- ? Brand = Alcoswitch