

SOLDERING/ASSEMBLY



www.eclipsetools.com

Mini-Soldering Station



- Precision temperature control: ~330°C (~626°F)
- Super slim, pen-like style for greater control and visibilty
- Specially designed for repairs to cell phones and PC boards
 Conductive soldering stand
- Dual voltage AC 110/220V

| Description | Part No. |
|--|----------|
| Mini-Soldering Station, 4-14 Watt Variable | 900-259 |
| Replacement Tip | 900-245 |

50W Soldering Station




| Description | Part No. |
|-------------------------------|----------|
| 50W Soldering Station | 900-066N |
| Replacement Tip (Pencil Type) | 900-073N |
| Replacement Tip (Chisel Type) | 900-074N |

20W-40W Soldering Station

• 20W-40W switchable solder station

Replacement Tip (Pencil Type)

- UL approved
- Comes with pencil tip




900-146


Lead-Free Soldering Station


- Three power consumption options (50W/65W/90W)
- Rapid heat-up and temperature stabilityTouch preheating and sensor in tip
- · temperature stability
- Separate tip and heater design to reduce replacement cost
- Heavy duty soldering station
- Auto shut-off function













| Part No. | 902-055 | | | |
|---------------------------------|--|--|--|--|
| Input Voltage/Frequency | AC100~120V, 50/60Hz | | | |
| Output Voltage/Frequency | AC24V 2~3.5A 60Hz | | | |
| Temperature Range | 200~500 | | | |
| Temperature Stability (no Load) | ±2 °C (±36 °F) | | | |
| Power Consumption (optional) | 50/65/90W | | | |
| Temperature Rise Time | 43/38/30sec (50/65/90W) 25~350°C | | | |
| Temperature Drop | 25 °C (77 °F) | | | |
| Heating Mode | CPU | | | |
| Auto Power Off | Yes (Not in use for 30 minutes) Yes (abnormal operation for 80 seconds) | | | |
| Temperature Display | LED | | | |
| ESD Housing | ABS & PC | | | |
| Outer Dimensions | 165X125X85mm | | | |
| Weight | 1.5Kg | | | |
| Standard Plug | Е | | | |
| Power Consumption | 90W AC24V | | | |
| Heater and Tips | Separate | | | |
| Touch Sensor for Preheating | Yes (3~5°C in 3 sec.) | | | |
| Heating Theory | Resistor | | | |
| Tip to Ground Resistance | Under 2Ω | | | |
| Tip to Ground Potential | Under 2mV | | | |
| Total Length (W/O cord) | 189mm | | | |
| Cord (with Soldering Iron) | 1.5M | | | |
| Weight (W/O cord) | 42g | | | |
| Weight | 420g | | | |
| Replacement Heater | 902-056 | | | |
| | | | | |

Soldering Station





902-173

Replacement Tip:




902-127 Sales unit: 5pcs/Bag

902-129(Standard)



902-131 Sales unit: 5pcs/Bag

Sales unit: 5pcs/Bag unit:inch



| Description | Voltage (v) | Consumption | Temperature | Replacement Heater | Station Size | Weight (g) | Part No. |
|-------------------|----------------|-------------|-------------|--------------------|---------------------------|------------|----------|
| Soldering Station | 110~120 48 (W) | | 150~420°C | 902-173 | 170(L) 116(W) 96(H) | 2000 | 902-091 |
| | | 48 (VV) | 160~480°C | | | | 902-092 |

Temperature Controlled Soldering Station

| Description | Voltage (v) | Consumption | Temperature | Replacement Heater | Station Size | Weight (g) | Part No. |
|--|-------------|-------------|-------------|--------------------|---------------------------|------------|----------|
| Temperature Controlled Soldering Station | 110~120 | 50 (W) | 250~480°C | 902-174 | 175(L) 103(W) 90(H) | 1100 | 902-093 |

Replacement Heater:

902-174

Replacement Tip:

| $\begin{array}{c ccccccccccccccccccccccccccccccccccc$ | 900-073N | $\emptyset \frac{\frac{3}{4}}{8} \qquad 1 \frac{\frac{7}{16}}{4}$ | 902-134 |
|--|-----------------------|---|----------|
| $\begin{array}{c ccccccccccccccccccccccccccccccccccc$ | 902-132 (Standard) | $\emptyset \frac{3}{16} \qquad 1 \frac{7}{16}$ | 902-135 |
| $\emptyset \frac{3}{8} \qquad 1\frac{7}{16}$ $\emptyset \frac{1}{4}$ | 902-133 | $\emptyset \frac{\frac{3}{4}}{8} = 1 \frac{7}{16}$ | 900-074N |

unit:inch

15W Soldering Iron



- Heats and cools very rapidly.3 "AA" Batteries not included.

| Description | Part No. |
|-------------------------|-----------|
| Cordless Soldering Iron | 902-047N |
| Replacement Tip | 902-047TN |



| Description | Part No. |
|-------------------------------|----------|
| 15 Watt | 900-044 |
| Replacement Tip (Pencil Type) | 900-050 |

30W Soldering Iron



| Description | Part No. |
|-------------------------------|----------|
| 30 Watt | 900-018N |
| Replacement Tip (Pencil Type) | 900-020N |

Soldering Gun



Allows soldering in seconds without long wait for tip to heat. Use low heat when working near senstitive parts and to lengthen tip life. High heat is instantly available when needed. Trigger switch turns gun on and off.140/100Watt 120V AC

| Description | Part No. |
|------------------|----------|
| Soldering Gun | 900-207 |
| Replacement Tips | 900-241 |

Digital Ultrasonic Cleaner

- Tightened lid design for effective noise reduction
- Improved products durability and safety by water resistance capability enhancement
 Cleans discs such as CDs, VCDs, DVDs, etc.
- · Use only plain tap water to clean
- Remove dirt effectively; results can be seen with bare eyes!
- Clean articles to shine just like new



| Item Number | 902-187 | Power Supply | AC 110~120V 50/60Hz |
|------------------|------------------|---------------|--|
| Dimensions | 8.3x6.2x4.9 inch | Power | 35W (110V) |
| Tank Size | 750ml | Timer Setting | 5 CYCLES: 180s, 280s, 380s, 480s, 90s |
| Standard Plug | A I I | Weight | 2.2 lbs |

Butane Torch



| Can be refilled | by standard butane c |
|-------------------------------------|------------------------|
| Uses a standar | rd type lighter refill |

| • Uses | a s | standar | d type | lighter | refill | |
|--------|-----|---------|--------|---------|--------|--|
| | | | | | | |

| Description | Part No. |
|--------------|----------|
| Butane Torch | 900-227 |

Flux Bottle



• i.d=0.6mm o.d=0.9mm

| Description | Part No. |
|----------------------|----------|
| Flux Bottle (2 pack) | 900-230 |

Liquid Dispenser Bottles



Item #: 900-253 Item #: 900-252 Item #: 900-251

- Polyethylene bottles are not chemically reactive
- Purity pump to prevent backwash of contaminants into container

| Description | Part No. |
|--------------------|----------|
| Bottle - 4oz/114ml | 900-251 |
| Bottle - 6oz/170ml | 900-252 |
| Bottle - 8oz/227ml | 900-253 |

• Ideal for blowing out hard-to-reach areas.

| Description | Part No. |
|-------------|----------|
| Blow Brush | 900-254 |

Solder Aid Tools



| Description | Part No. |
|------------------|----------|
| Solder Aid Tools | 900-250 |

6 PC Soldering Aid Set



• 6 Double-ended picks and brushes

| Description | Part No. |
|------------------------|----------|
| 6 PC Soldering Aid Set | 900-100 |

Desoldering Tools



| Description | Part No. |
|-----------------------------|----------|
| Desoldering Pump | 900-001N |
| Mini Desolder Pump | 900-003 |
| Mini Desolder Pump | 900-004 |
| Mini Desolder Pump | 900-161 |
| Replacement Tip for 900-001 | 900-006N |
| Replacement Tip for 900-003 | 900-007 |
| Replacement Tip for 900-004 | 900-008 |
| Replacement Tip for 900-161 | 900-175 |

Item #: 900-175

Vacuum Pick-up Tool

Function:

- The hand-held SMD vacuum pick up tool is ideal for picking up and moving large or small electronic components.
- Lightweight, portable and suitable for picking and placing small components with weight to up 50 grams and having a flat surface, dilly packages and surface mount components, etc. And its new high-power probes have longer holding action.





| Description | Part No. |
|---------------------|----------|
| Vacuum Pick-up Tool | 902-115 |

5"/6" Straight and Curved Forceps



| Insulated handles | | |
|---------------------------------|----------|--|
| Description | Part No. | |
| 5" Straight Forceps (insulated) | 900-058 | |
| 5" Curved Forceps (insulated) | 900-059 | |
| 6" Straight Forceps (insulated) | 900-181 | |
| 6" Curved Forceps (insulated) | 900-222 | |

Vacuum Pick-Up Tool



• Ideal for picking and placing surface mount devices (SMD's)

| Description | Part No. |
|---------------------|----------|
| Vacuum Pick-Up Tool | 900-238 |

Mini Soldering Stand (2PCS/PACK)



- · 2 position iron holder stand
- · Built-in sponge tray

| | Description | Part No. |
|---|----------------------------------|----------|
| Ì | Mini Soldering Stand (2PCS/PACK) | 902-095 |



Helping Hands Octopus Clamp Kit





| Description | Part No. |
|---------------------------------|----------|
| Helping Hands Octopus Clamp Kit | 902-227 |

Ionized Air Blowers (AC 110V/60HZ)

Features:


- · Compact, lightweight, and quiet; ideal for field use.
- Adjustable airflow output for greater worker comfort.
- True laminar flow reducing ion recombination and emitter contamination.
- Easy cleaning and replaceable blower.

| Voltage | AC 110V 60 HZ |
|---------------------------------|-----------------------------|
| Current | ≤0.25Amp(AC110V) |
| Air Volume output | Fan speed Flow 20~110CFM |
| Air Flow characteristics | 16"x24" Area Coverage |
| Operating Temperature | 32°F(0°C)~122°F(50°C) |
| Enclosure | Stainless steel |
| Finish | Powder Coat |
| Size | 10"x7"x4" |
| Ion Balance (offset voltage) | 0V+/-10V |
| Weight (lbs) | 1.56 |
| Individual Packing | Color Box |



| Description | Part No. |
|-------------------------------------|----------|
| Ionized Air Blowers (AC 110V/60HZ) | 902-107 |

Solder Tip Cleaner



No temperature drop as in conventional sponges.

· Cleans better than conventional sponges.

Anti-slip pad.

| Description | Part No. |
|---------------------------------|----------|
| Solder Tip Cleaner | 900-242 |
| Solder Tip Cleaner- 5 pk refill | 900-243 |

Helping Hands

- The practical helper for soldering work for electronics and model-making.
 Holding clamps adjustable in many ways, complete
- with magnifying glass 3.5"(90mm) dia:2X.

 Sturdy stand.



| Description | Magnification | Part No. |
|---------------|---------------|----------|
| Helping Hands | 2X | 902-094 |

Soldering Stand w/Solder Reel Holder



- Holds standard soldering iron
- · Sponge for cleaning tip
- · Holds roll of solder for easy, one-handed dispensing
- Heavy weighted base keeps unit stable

| Description | Part No. |
|--------------------------------------|----------|
| Soldering Stand w/Solder Reel Holder | 900-099 |

Helping Hands Soldering Aid



- Magnifying Lens Soldering Iron Holder Sponge

| Description | Part No. |
|-----------------------------|----------|
| Helping Hands Soldering Aid | 900-206 |

Soldering Tool Stand



· Holds up to two soldering irons • All holders adjustable for maximum comfort

| Description | Part No. |
|----------------------|----------|
| Soldering Tool Stand | 900-101 |

Solder Iron Stand



- Small stand for holding soldering iron
- · Comes with a sponge

| Description | Part No. |
|-------------------|----------|
| Solder Iron Stand | 900-016 |

"Helping Hands" Soldering Aid



- "Helping Hands" Soldering Aid

- Table top, weighted base
 Multi-dimensional adjustment capability
 Alligator style clips for holding subject work

| • | , | • | , | |
|---------|---------|-------|---|----------|
| Descrip | otion | | | Part No. |
| Without | Magn | ifier | | 900-015 |
| With Ma | agnifie | r | | 900-037 |

Mini - Vacuum Cleaner



• 3 "AA" batteries, not included

| Description | Part No. |
|-------------------|----------|
| Mini - Vacuum Kit | 900-270 |

Breadboard Accessory



- 70pcs of 22 AWG solid wires
- Variety of colors 14 lengths x 5pcs each
- Pre-cut, Pre Stripped and Pre-formed on each end.
- Completely Reusable (2,5,7,10,12,15,17,20,22,25,50,75,100 and 125mm)

| Description | Part No. |
|-----------------------------------|----------|
| Breadboard Accessory - 70 pcs/set | 900-271 |

Breadboard Accessory



- 350pcs of 22 AWG solid wires Variety of colors
- 14 lengths x 25pcs each
- Pre-cut, Pre Stripped and Pre-formed on each end.
- · Completely Reusable
- (2,5,7,10,12,15,17,20,22,25,50,75,100 and 125mm)

| Description | Part No. |
|------------------------------------|----------|
| Breadboard Accessory - 350 pcs/set | 900-272 |

Item #: 900-248 1580 tie points Edge plate can easy fold up Item #: 900-249 2420 tie points

Breadboards

Expandable by combining several boards together to meet your different requirement

Item #: 900-247 840 tie points

Round hole designed for easy plug and pull
 Waterproof material made of ABS & phosphor bronze with good flexibility and electric conductivity

| Description | Application | Part No. |
|-----------------------|-----------------|----------|
| Round Hole Breadboard | 840 tie points | 900-247 |
| Round Hole Breadboard | 1580 tie points | 900-248 |
| Round Hole Breadboard | 2420 tie points | 900-249 |