Product data sheet Characteristics

9007MS10S0300 LIMIT SWITCH 240VAC 10AMP MS +OPTIONS

Product availability: Stock - Normally stocked in distribution facility





Price**: 99.00 USD



Main

Range of product	9007	<u></u>
Series name	Miniature potted	
Product or component type	Limit switch	
Device short name	9007MS/ML	
Sensor design	Miniature	> <u></u>
Body type	Fixed	
Head type	Plunger head	
Material	Metal	
Body material	Cast zinc	
Number of poles	1	i.
		ä.

Complementary

Fixing mode	By the body	to
Movement of operating head	Linear	S not
Type of operator	Spring return plunger stainless steel booted	
Type of approach	Vertical approach, 1 direction	fe for
Switch actuation	On end	— stitu:
Contacts type and composition	NC-NO	
Switch function	SPDT	— se
Contact form	Form C	—tende
Contacts material	Silver contacts	<u>:</u>
Contact operation	Snap action	— <u>s</u>
Positive opening	Without	interior
Electrical connection	Pre-wired cable bottom	— i
Type of cable	SJTO AWG 18), 2.74 m (9 ft), yellow	— sic
Terminals description ISO n°1	(red)NC (white)NO (black)com	isclaimer: T

1			_		_ 11	_	\		_	_
- ((ar	ee	n-	·V	eII	O	W	เด	ın	С

Wire insulation material	PVC
Maximum force for tripping	80 ozf
[le] rated operational current	6 A 120 V AC, A300 NEMA rating designation 3 A 240 V AC, A300 NEMA rating designation 5 A 28 V DC
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	300 V 3)UL 508 300 V 3)CSA C22.2 No 14
Electrical durability	100000 cycles
Mechanical durability	10000000 cycles
Marking	UL CSA CE
Sale per indivisible quantity	1
Height	44.45 mm (1.75 in)
Width	39.62 mm (1.56 in)
Depth	15.75 mm (0.62 in)
Net weight	0.54 kg (1.2 lb(US))

Environment

01 1 1 1	05 0 150 00000 0 07
Shock resistance	35 gn 9 ms IEC 60068-2-27
Vibration resistance	10 gn 751200 Hz)IEC 60068-2-6
NEMA degree of protection	NEMA 1 Nema type 250
	NEMA 2 Nema type 250
	NEMA 4 Nema type 250
	NEMA 6 Nema type 250
	NEMA 6P Nema type 250
IP degree of protection	IP67 IEC 60529
Ambient air temperature for operation	-40104 °C (-40220 °F)
Ambient air temperature for storage	-40104 °C (-40220 °F)
Protective treatment	Epoxy powder coat
Product certifications	CSA
	UL
	CE
Standards	E78403
	LR 25490 Class 32 11 03

Ordering and shipping details

Category	22431 - LIMIT SWITCHES,TYPE 9007MS
Discount Schedule	DS1
GTIN	00785901000228
Package weight(Lbs)	0.54 kg (1.2 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov		
REACh Regulation	REACh Declaration		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		

Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		

18 months

Warranty