

**Connecting elements**  
**H0,75/12D GR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



- supplied loose in polybag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |   |
|------------|---|
| Type       | H0,75/12D GR                                  |
| Order No.  | <a href="#">9019030000</a>                    |
| Version    | Wire-end ferrule, insulated, 8 mm, 6 mm, grey |
| GTIN (EAN) | 4008190127787                                 |
| Qty.       | 500 pc(s).                                    |
| Packaging  | loose   |

Creation date April 14, 2020 4:45:35 AM CEST

Catalogue status 03.04.2020 / We reserve the right to make technical changes.

**Data sheet**

**Connecting elements  
H0,75/12D GR**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |         |                |            |
|------------|---------|----------------|------------|
| Width      | 12 mm   | Width (inches) | 0.472 inch |
| Net weight | 0.076 g |                |            |

**Technical data**

|         |           |
|---------|-----------|
| Version | insulated |
|---------|-----------|

**Wire-end ferrules**

|   |                      |                               |             |
|---|----------------------|-------------------------------|-------------|
| Collar diameter (D2)                    | 2.8 mm               | Colour code                   | DIN         |
| Conductor cross-section                 | 0.75 mm <sup>2</sup> | Contact surface diameter (D1) | 1.2 mm      |
| Contact surface length (L2)             | 6 mm                 | L1 in mm                      | 12 mm       |
| Metal sleeve thickness (S1)             | 0.15 mm              | Military designation          | T 20A 005 A |
| Plastic collar thickness (S2)           | 0.25 mm              | Stripping length              | 8 mm        |
| Wire connection cross section AWG, max. | AWG 18               |                               |             |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0   | EC000005    |
| eClass 9.0  | 27-40-02-01 | eClass 9.1 | 27-40-02-01 |
| eClass 10.0 | 27-40-02-01 | UNSPSC     | 31-16-31-02 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |  |
|--------------------|--|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>   |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>   |
| Engineering Data   | <a href="#">STEP</a>   |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |

**Data sheet**

**Connecting elements**  
**H0,75/12D GR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

**Drawing**

