


**Connecting elements
H2,5/19D BL**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



- supplied loose in polybag
- DIN colour code
- other colour code

General ordering data

| | |
|------------|---|
| Type | H2,5/19D BL |
| Order No. | 9019170000 |
| Version | Wire-end ferrule, insulated, 14 mm, 12 mm, blue |
| GTIN (EAN) | 4008190178024 |
| Qty. | 500 pc(s). |
| Packaging | loose |

**Connecting elements
H2,5/19D BL**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|------------|--------|----------------|------------|
| Width | 19 mm | Width (inches) | 0.748 inch |
| Net weight | 0.18 g | | |

Technical data

| | |
|---------|-----------|
| Version | insulated |
|---------|-----------|

Wire-end ferrules

| | | | |
|---|---------------------|-------------------------------|-------------|
| Collar diameter (D2) | 4.2 mm | Colour code | DIN |
| Conductor cross-section | 2.5 mm ² | Contact surface diameter (D1) | 2.2 mm |
| Contact surface length (L2) | 12 mm | L1 in mm | 19 mm |
| Metal sleeve thickness (S1) | 0.15 mm | Military designation | T 20A 017 A |
| Plastic collar thickness (S2) | 0.25 mm | Stripping length | 14 mm |
| Wire connection cross section AWG, max. | AWG 14 | | |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000005 | ETIM 7.0 | EC000005 |
| eClass 9.0 | 27-40-02-01 | eClass 9.1 | 27-40-02-01 |
| eClass 10.0 | 27-40-02-01 | UNSPSC | 31-16-31-02 |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|--------------------|--|
| Brochure/Catalogue | CAT 6 TOOLS 15/16 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |

Data sheet

**Connecting elements
H2,5/19D BL**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Drawing

