Product data sheet Characteristics

9080GM6

Terminal Block, box lug connector, 30 A, 600 VAC/DC, natural colored block

Product availability: Stock - Normally stocked in distribution facility

Price**: 1.80 USD



9080GM6 has not been replaced. Please contact your customer care center for more information.

Main

Range of product	9080G	
Product	Terminal block standard	
Product or component type	Terminal block	
Color	Natural	
Quantity	Set of 50	

Complementary

1		
Voltage Rating	600 V AC/DC	
Current Rating	30 A UL 30 A CSA	
Wire Size	AWG 22AWG 10 copper	:
Mounting Type	9080GH track 35 mm DIN rail	:
Certifications	CE CSA file 62144 class 6228 01 UL recognized E60616 CCN XCFR2	
Protection Type	Fingersafe DIN 57470	
Electrical Connection	Zinc plated steel box lugs	
Material	Nylon block Tin plated brass busbar	
Ambient air temperature for operation	-40125 °C (-40257 °F)	
Electrical Connrection Tightening Torque	Lug zinc plated steel 0.790.90 N.m (78 lbf.in) : AWG 22AWG 10 copper)	
Height	46.23 mm (1.82 in)	
Width	43.69 mm (1.72 in)	
Depth	5.97 mm (0.235 in)	
Density	51 per foot	
Compatible End Barrier	ible End Barrier GM6B	

Ordering and shipping details

	11 0	
Category		21702 - 9080 G (NOT GCB)

Discount Schedule	nedule CP5	
GTIN	00785901743927	
Package weight(Lbs)	0.01 kg (0.02 lb(US))	
Returnability	Yes	
Country of origin	MX	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
EU RoHS Directive	Compliant EU RoHS Declaration	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	

Contractual warranty

Warranty	18 months	5