


**MICRO SWITCH**  
a Honeywell Division

FED. MFG. CODE 91929

**MINIATURE PRECISION  
LIMIT SWITCH**

CATALOG LISTING

**914CE20-9**



2.000 MAX  
OPERATING POSITION  
IN ALL DIRECTIONS  
EXCEPT PULL  
(.5 FROM TIP OF  
ROD ACTUATOR)

NEOPRENE SEAL

2X  $\varnothing$  .200 $\pm$ .010  
MOUNTING HOLES  
( $\varnothing$  .40 C'BORE  
.24 DEEP)

$.300 \pm .010$

1.732 MAX

108.000 MIN

P.V.C. SHEATHED CABLE  
18/4 S.J.T.O.

.630 MAX

$.984 \pm .010$

1.575 MAX

8.937 MAX


**NOTES**

1 - ZINC HOUSING FINISHED WITH GRAY PAINT

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



**CHARACTERISTICS**

OPERATING FORCE — — — 2 OZ MAX

**ELECTRICAL DATA**

CONTACT ARRANGEMENT  
S P D T

5A - 250 VAC  
1/10HP - 125 OR 250 VAC



**SCALE FULL**

DO NOT  
SCALE PRINT

**UNLESS OTHERWISE SPECIFIED  
TOLERANCES ARE**

ONE PLACE (.01)  $\pm$ .030

TWO PLACE (.00)  $\pm$ .015

THREE PLACE (.000)  $\pm$ .005

ANGLES  $\pm$

WEIGHT

914CE20-9

**M**

DRAWING  
NUMBER

3

ISSUE

REPLACES

RELEASE NO. PR-7324

CHECK

**REVISIONS**

A	CO	69061
S	A	V
		31 AUG 91

CHECK

DDM/CAD

DRAWN

CHECK

S A V 31 AUG 91