RF Connectors



<u>921 - 320 - 511 - 583 F</u> **SERIES BODY MATERIAL** CROSS / REF **IMPEDANCE STYLE CONNECTOR TYPE TERMINATION / PROFILE** CONTACT PLATING FILTERED CONNECTOR

FEATURES

- •Broad range of RF interconnect products available
- **UHF** •Standard / Miniature offering:

50 & 75 OHM

BNC TNC

•Sub miniature offering: **SMA**

SMB SMC

- Coupling styles include: 2-stud bayonet; threaded; snap on and slide on

Additional connectors including custom solutions

- Cable mount and PCB mount available
- •Meets MIL C 39012 specifications

APPLICATIONS

- Broadcast
- Satellite Communications
- Telecommunications
- Test and Measurement
- •LAN
- Instrumentation

S	Ε	R	ΙE	5

SERIES	
BNC	92
1.5/5.6	93
N	94
SMA	95
SMZ	95
SMC	96
F	97
SMB	98
ADAPT.	99

BODY MATERIAL

- 1 = BRASS
- 2 = DIECAST 3 = DUAL BNC
- 4 = SMZ

CROSS / REF

COMPETITION (31 - 320)900 - SPÉCIALS

IMPEDANCE

- 5 = 50 OHMS 7 = 75 OHMS
- 0 = N/A

STYLE

- 1 = STRAIGHT
- 2 = BULKHEAD
- 3 = RIGHT ANGLE PCB (METAL BODY)
- 4 = RIGHT ANGLE PCB (PLASTIC BODY)
- 5 = T ADAPTER
- 6 = TERMINATOR
- 7 = RIGHT ANGLE ADAPTER
- 8 = RIGHT ANGLE
- 9 = STRAIGHT ADAPTER

CONNECTOR TYPE

- 1 = PLUG (MALE) 2 = JACK (FEMALE)
- 3 = ADAPTER
- 4 = LOW PROFILE BNC PCB R/A WHITE VALOX HOUSING
- 5 = LOW PROFILE BNC PCB R/A METAL HOUSING
- 6 = STANDARD PROFILE BNC PCB R/A WHITE VALOX HOUSING
- 7 = STANDARD PROFILE BNC PCB R/A METAL HOUSING
- 8 = PLUG TERMINATOR
- 9 = SOLDER / BODY PLUG (MALE) SMA / SMB
- 0 = SOLDER / BODY JACK (FEMALE) SMA / SMB
- A = .500 HIGH PROFILE R/A METAI B = .500 HIGH PROFILE R/A PLASTIC
- C = VERTICAL METAL BODY PCB
- D = VERTICAL PLASTIC BODY PCB
- E = PANEL MOUNT SQ.

TERMINATION / PROFILE

- 10 = SOLDER CUP
- 20 = ADAPTER
- 30 = R/A PCB 40 = TERMINATOR
- 60 = PANEL MOUNT
- 50 = STRAIGHT PCB
- 58 = RG58 (CRIMP)
- 59 = RG59 (CRIMP)
- 74 = RG174 (CRIMP)
- 79 = RG179 (CRIMP)
- 9X = SPECIALS

CONTACT PLATING

- 0 = NICKEL / TIN PLATED 1 = GOLD FLASH
- 2 = 15 MICRO INCH GOLD
- 3 = 30 MICRO INCH GOLD





