PHILIPS Lighting



PL-Q 4 Pin

PL-Q 28W/827/4P 1CT/10BOX

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 4-pin version is designed for operation on electronic gear.

Product data

General Information					
Cap-Base	GR10Q [GR10q]				
Life to 50% Failures Preheat (Nom)	13000 h				
LSF Preheat 2000 h Rated	99 %				
LSF Preheat 4000 h Rated	98 %				
LSF Preheat 6000 h Rated	95 % 89 % 22 %				
LSF Preheat 8000 h Rated					
LSF Preheat 16000 h Rated					
LSF Preheat 20000 h Rated	4 %				
Light Technical					
Color Code	827 [CCT of 2700K]				
Luminous Flux (Nom)	2050 lm				
Luminous Flux (Rated) (Nom)	2050 lm				
Color Designation	Incandescent White				
Correlated Color Temperature (Nom)	2700 K				
Luminous Efficacy (rated) (Nom)	73.2 lm/W				
Color Rendering Index (Nom)	82				
LLMF 2000 h Rated	90 %				
LLMF 4000 h Rated	86 %				
LLMF 6000 h Rated	83 %				
LLMF 8000 h Rated	80 %				


LLMF 12000 h Rated	79 %	
LLMF 16000 h Rated	78 %	
LLMF 20000 h Rated	78 %	
Operating and Electrical		
Power (Nom)	24.8 W	
Lamp Current (Nom)	0.320 A	
Temperature		
Design Temperature (Nom)	25 °C	
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Cap-Base Information	4 Pins	
Approval and Application		
Energy Efficiency Label (EEL)	А	
Mercury (Hg) Content (Nom)	4 mg	
Energy Consumption kWh/1000 h	31 kWh	

PL-Q 4 Pin

Product Data				
Full product code	871150026991125			
Order product name	PL-Q 28W/827/4P 1CT/10BOX			
EAN/UPC - Product	8711500269911			
Order code	927939382740			
Numerator - Quantity Per Pack	1			


Numerator - Packs per outer box	10				
Material Nr. (12NC)	927939382740				
Net Weight (Piece)	127.000 g				
ILCOS Code	FSS-28/27/1B-E-GR10q				

Dimensional drawing




PL-Q 28W/827/4P

Photometric data







Product	U (max)	D (max)	D1 (max)	C (max)	C1 (max)	F (max)	E (max)
PL-Q 28W/	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
827/4P 1CT/							
10BOX							



LDPO_PLQ4P_827-Spectral power distribution Colour

Lifetime






LDLM_PLQ4P_0001-Lumen maintenance diagram

PL-Q 4 Pin

Lifetime



LDLE_PLQ4P_0001-Life expectancy diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2020, March 19 - data subject to change