



TABLE

ITEM NO	L
9301-2	1000mm±20mm
9301-2	2000mm±20mm
9301-3	3000mm±30mm
9301-5	5000mm±30mm
9301-10	10000mm±30mm

- 1. CABLE: NO UL, 28AWG(7/0.127), TINNED AND STRANDED COPPER WIRE
 INSULATOR: PVC, ID: 0.85mm, CABLING: 9C+DRAIN WIRE
 SHIELD: AL/MY COVERAGE
 JACKET: PVC, COMPLIANCE ROHS, COLOR: BEIGE, O.D: 5mm
- 2. 1PCS CONNECTOR: D-SUB 9 WAYS MALE SOLDER TYPE CONNECTOR
 INSULATOR: P.B.T.+GLASS FIBER, COLOR: BLUE
 CONTACT: COPPER ALLOY, GOLD FLASH OVER NICKEL PLATED
 SHELL: NICKEL PLATED.
 CONNECTOR COMPLIANCE ROHS
- 3. 1PCS CONNECTOR: D-SUB 9 WAYS FEMALE SOLDER TYPE CONNECTOR
 INSULATOR: P.B.T.+GLASS FIBER, COLOR: BLUE
 CONTACT: COPPER ALLOY, GOLD FLASH OVER NICKEL PLATED
 SHELL: NICKEL PLATED.
 CONNECTOR COMPLIANCE ROHS
- 4. HOOD: PVC MOLDED TYPE WITH FOIL SHIELDED ON INNER
 ON INNER MOLD AND INJECTION OUTER MOLD WITH
 THUMB SCREW #4-40 UNC
 COLOR: BEIGE, COMPLIANCE ROHS
- 5 Fulfill ROHS Guideline
- 6. ELECTRONIC TEST: 100% OPEN SHORT+MISS WIRE TEST

PIN OUT

DB9PIN MALE(P1)	WIRE	DB9PIN FEMALE(J1)
1		1
2		2
3		3
4		4
5		5
6		6
7		7
8		8
9		9
SHELL	DRAIN WIRE	SHELL

PART NO	SHEET NO 1	THIRD ANGLE PROJECTION
TITLE: DB9 PIN MALE TO DB9 PIN FEMALE BEIGE COLOR	SCALE N.T.S	DRAWN BY & DATE
	SIZE A4	CHECKED BY & DATE
	UNIT	APPROVED BY & DATE
DWN NO	<input checked="" type="checkbox"/> MM <input type="checkbox"/> INCH	