



**Product:** <u>9421</u> ☑

Electronic, 8 C #22 Str TC, PVC Ins, PVC Jkt, CMG

# **Product Description**

Electronic, 8 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

### **Technical Specifications**

### **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

# **Physical Characteristics (Overall)**

### Conductor

Element	AWG	Stranding	Ma	aterial	No. of Conductors
Conductor(s)	22	7x30	TC - Tin	nned Copper	8
Conductor Count: 8		8			

#### Insulation

Element	Material	Nominal Wall Thickness
Conductor(s)	PVC - Polyvinyl Chloride	0.011 in

### Color Chart



### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.229 in	0.032 in

## **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR 15.6 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Conductor 34 pF/ft

### Inductance

Nominal Inductance

### Current

# Max. Recommended Current [A] 2.1 Amps per conductor @ 25°C A

### Voltage

UL Description	UL Voltage Rating	
CMG	300 V	
UL AWM 2576	150 V	

# **Temperature Range**

UL Temp Rating:	80°C (UL AWM 2576)
Operating Temp Range:	-20°C to +80°C

# **Mechanical Characteristics**

Bulk Cable Weight:	33 lbs/1000ft
Max Recommended Pulling Tension:	71 lbs
Min Bend Radius/Minor Axis:	2.5 in

### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	2576
CSA AWM Specification:	FT4
CPR Euroclass:	Eca

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

# Suitability

Suitability - Indoor:	Yes	

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V (CMG), 150 V UL AWM 2576)

## Plenum/Non-Plenum

Plenum (Y/N):	No
, ,	

## **Part Number**

### Variants

Item #	Color	UPC
9421 060100	Chrome	612825244257
9421 0601000	Chrome	612825244264
9421 060500	Chrome	612825244271
9421 0605000	Chrome	612825244288
9421 060U1000	Chrome	612825244233

Revision Number: 0.290 Revision Date: 05-19-2020

© 2020 Belden, Inc

Update and Revision:

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.