

Datasheet

Item No. 96.032.4154.3

Male connector with strain relief RST25I3S S1 ZR2 V BC

Connector RST25i3, 3 pole, male, screw connection, 250V/25A, for cable diameters 10-14 mm, color of coding: concrete gray, color of housing: black



Item No.	96.032.4154.3
EAN	4015573864108
order unit	100 Piece(s)

Approvals



Technical data

**General**

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Concrete gray

**Connection Data**

Connection cross section solid	4 mm <sup>2</sup>
Connection cross section stranded	4 mm <sup>2</sup>
Terminations per pole	1

**Model**

Model	Plug
Number of poles	3
Connection type	Screw connection
Degree of protection (IP)	IP66/IP68

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C

Surface finish	Silver-plated
<b>Dimensions</b>	
Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Drawings

for cable diameter 10-14mm  
für Kabeldurchm. 10-14mm  
color: black, similar RAL 9005  
Farbe: schwarz, öhnl. RAL 9005

color: grey, similar RAL 7023  
Farbe: betongrau, öhnl. RAL 7023

Type: RST2513S S1AZR2V BG03

Verpackungseinheit: je 100 Stück  
packaging unit: per 100

STECKERTEIL MIT ZUGENTLASTUNG  
male connector with cord grip  
Schraubanschluß ohne Drahtschutz/Screw connection w/ fixed wire protection