Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

9930 Hook-up/Lead - UL AWM Style 1007



For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, PVC insulation. Rated 80°C, 300V. Rated 600V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

		Color		Item Desc	
		No			
		VW-1			
-					
loHS):		Yes			
re & Cable):		Yes			
		Yes			
C (WEEE):		Yes			
		10/01/2005			
		Yes			
C (ELV):		Yes			
		Yes			
U (ROHS II):		Yes			
		300 V RMS, 80°C			
2	grame	UL Style 1007 (300 V 80°C)			
		overall)			
	• • •				
ristics (Overall)		1 200 lbs/1000 ft			
eter:		0.044 in.			
e 0.016	0.015				
uctors:		1			
7x38 TC - Tinned	Copper				
Stranding Conductor	Naterial				
	7x38 TC - Tinned (uctors: Wall Thickness (in.) Je 0.016 eter: ristics (Overall) cions and Agency	wall Thickness (in.) Min. Avg. Wall (in.) ie 0.016 other 0.015 eter:	TC - Tinned Copper uctors: 1 Wall Thickness (in.) Min. Avg. Wall (in.) ie 0.016 0.015 eter: 0.044 in. ristics (Overall) stores and Agency Compliance (Overall) A Environmental Programs UL Style 1007 (300 V 80°C) S00 V RMS, 80°C EU (ROHS II): Yes SC (ELV): Yes SC (ROHS): Yes Date (mm/dd/yyyy): 10/01/2005 SC (BFR): Yes re & Cable): Yes Sc (BFR): Yes Yes Yes Sc (BFR): Yes Yes Yes <	Tx38 TC - Tinned Copper uctors: 1 Vali Thickness (in.) Min. Avg. Wali (in.) 0.015 eter: 0.044 in. ristics (Overall) 1.200 lbs/1000 ft. ristics (Overall) 1.200 lbs/1000 ft. ristics and Agency Compliance (Overall) 1.200 lbs/1000 ft. Etericons and Agency Compliance (Overall) Yes Etericons and Agency Compliance (Overall) Yes	Tx38 Tc - Tinned Copper uctors: 1 Wall Thickness (in.) Min. Avg. Wall (in.) le [0.016 0.015 eter: 0.044 in. ristics (Overall) 1.200 lbs/1000 ft. ristics (Overall) 1.200 lbs/1000 ft. cions and Agency Compliance (Overall) UL Style 1007 (300 V 80°C) cions and Agency Compliance (Overall) 300 V RMS, 80°C cions and Agency Compliance (Overall) Yes ci (EUV): Yes ci (ELV): Yes ci (ELV): Yes ci (ELV): Yes ci (ELV): Yes ci (EF

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9930 0011000	1,000 FT	2.000 LB	BROWN	P	30 STR PVC BRN
9930 002100	100 FT	0.200 LB	RED		30 STR PVC RED
9930 0021000	1,000 FT	2.000 LB	RED	Р	30 STR PVC RED
9930 003100	100 FT	0.200 LB	ORANGE	1	30 STR PVC ORG
9930 0041000	1,000 FT	2.000 LB	YELLOW	P	30 STR PVC YEL
9930 005100	100 FT	0.200 LB	GREEN, DARK	1	30 STR PVC GRN
9930 0051000	1,000 FT	2.000 LB	GREEN, DARK	P	30 STR PVC GRN
9930 007100	100 FT	0.200 LB	VIOLET		30 STR PVC VIO

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

9930 Hook-up/Lead - UL AWM Style 1007

9930 008100	100 FT	0.200 LB	GRAY		30 STR PVC GRY
9930 009100	100 FT	0.200 LB	WHITE		30 STR PVC WHT
9930 0091000	1,000 FT	2.000 LB	WHITE	Р	30 STR PVC WHT
9930 010100	100 FT	0.200 LB	BLACK		30 STR PVC BLK
9930 0101000	1,000 FT	2.000 LB	BLACK	Р	30 STR PVC BLK
9930 013100	100 FT	0.200 LB	BLUE, DARK		30 STR PVC DBLU
9930 0131000	1,000 FT	2.000 LB	BLUE, DARK	Р	30 STR PVC DBLU

Notes: P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2 Revision Date: 10-01-2008

© 2016 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is denied on the product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).