# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



## 9930 Hook-up/Lead - UL AWM Style 1007

For more Information please call

1-800-Belden1



### **General Description:**

Tinned copper conductor, PVC insulation. Rated 80°C, 300V. Rated 600V peak for electronic circuits, and

#### internal wiring of electronic and electrical equipment. **Physical Characteristics (Overall)** Conductor AWG: # Conductors AWG Stranding Conductor Material 7x38 TC - Tinned Copper 30 **Total Number of Conductors:** 1 Insulation Insulation Material: Wall Thickness (in.) Min. Avg. Wall (in.) **Insulation Material** PVC - Polyvinyl Chloride | 0.016 0.015 **Overall Insulation Overall Cable** Overall Nominal Diameter: 0.044 in. **Mechanical Characteristics (Overall) Bulk Cable Weight:** 1.200 lbs/1000 ft. **Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs** UL AWM Style: UL Style 1007 (300 V 80°C) **UL Rating:** 300 V RMS, 80°C

### EU Directive 2011/65/EU (ROHS II): Yes EU CE Mark: Yes EU Directive 2000/53/EC (ELV): EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 10/01/2005 EU Directive 2002/96/EC (WEEE): Yes EU Directive 2003/11/EC (BFR): Yes CA Prop 65 (CJ for Wire & Cable): Yes MII Order #39 (China RoHS): Yes Flame Test **UL Flame Test:** VW-1

# Plenum (Y/N): **Put Ups and Colors:**

Plenum/Non-Plenum

| Item #       | Putup    | Ship Weight | Color       | Notes | Item Desc      |
|--------------|----------|-------------|-------------|-------|----------------|
| 9930 0011000 | 1,000 FT | 2.000 LB    | BROWN       | Р     | 30 STR PVC BRN |
| 9930 002100  | 100 FT   | 0.200 LB    | RED         |       | 30 STR PVC RED |
| 9930 0021000 | 1,000 FT | 2.000 LB    | RED         | Р     | 30 STR PVC RED |
| 9930 003100  | 100 FT   | 0.200 LB    | ORANGE      |       | 30 STR PVC ORG |
| 9930 0041000 | 1,000 FT | 2.000 LB    | YELLOW      | Р     | 30 STR PVC YEL |
| 9930 005100  | 100 FT   | 0.200 LB    | GREEN, DARK |       | 30 STR PVC GRN |
| 9930 0051000 | 1,000 FT | 2.000 LB    | GREEN, DARK | Р     | 30 STR PVC GRN |
| 9930 007100  | 100 FT   | 0.200 LB    | VIOLET      |       | 30 STR PVC VIO |

No

Page 1 of 2

# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



## 9930 Hook-up/Lead - UL AWM Style 1007

| 9930 008100  | 100 FT   | 0.200 LB | GRAY       |   | 30 STR PVC GRY  |
|--------------|----------|----------|------------|---|-----------------|
| 9930 009100  | 100 FT   | 0.200 LB | WHITE      |   | 30 STR PVC WHT  |
| 9930 0091000 | 1,000 FT | 2.000 LB | WHITE      | Р | 30 STR PVC WHT  |
| 9930 010100  | 100 FT   | 0.200 LB | BLACK      |   | 30 STR PVC BLK  |
| 9930 0101000 | 1,000 FT | 2.000 LB | BLACK      | Р | 30 STR PVC BLK  |
| 9930 013100  | 100 FT   | 0.200 LB | BLUE, DARK |   | 30 STR PVC DBLU |
| 9930 0131000 | 1,000 FT | 2.000 LB | BLUE, DARK | Р | 30 STR PVC DBLU |

#### Notes:

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2 Revision Date: 10-01-2008

© 2015 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Page 2 of 2