Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



9985 Hook-up/Lead - UL AWM Style 1061

For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

Physical Characteristics (Overall)

Conducto

AWG:



Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.010

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.039 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 1.500 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	300 V RMS, 80°C	
UL Type:	AWM 1061	
CSA Rating:	300 V RMS, 80°C	
CSA Type:	AWM I, A/B	
EU Directive 2011/65/EU (ROHS II):	Yes	
EU CE Mark:	Yes	
EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2002/95/EC (RoHS):	Yes	
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005	
EU Directive 2002/96/EC (WEEE):	Yes	
EU Directive 2003/11/EC (BFR):	Yes	
CA Prop 65 (CJ for Wire & Cable):	Yes	
MII Order #39 (China RoHS):	Yes	
Flame Test		
UL Flame Test:	VW-1	
CSA Flame Test:	FT1	
Plenum/Non-Plenum		

Plenum (Y/N): Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9985 001100	100 FT	0.200 LB	BROWN		26 STR PVC BRN
9985 0011000	1,000 FT	2.000 LB	BROWN	Р	26 STR PVC BRN
9985 002100	100 FT	0.200 LB	RED		26 STR PVC RED
9985 0021000	1,000 FT	2.000 LB	RED	Р	26 STR PVC RED
9985 003100	100 FT	0.200 LB	ORANGE		26 STR PVC ORG

No

Page 1 of 2 08-26-2016

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



9985 Hook-up/Lead - UL AWM Style 1061

9985 0031000	1,000 FT	2.000 LB	ORANGE	P	26 STR PVC ORG
9985 004100	100 FT	0.200 LB	YELLOW		26 STR PVC YEL
9985 0041000	1,000 FT	2.000 LB	YELLOW	P	26 STR PVC YEL
9985 005100	100 FT	0.200 LB	GREEN, DARK		26 STR PVC GRN
9985 0051000	1,000 FT	2.000 LB	GREEN, DARK	P	26 STR PVC GRN
9985 008100	100 FT	0.200 LB	GRAY		26 STR PVC GRY
9985 0081000	1,000 FT	2.000 LB	GRAY	P	26 STR PVC GRY
9985 009100	100 FT	0.200 LB	WHITE		26 STR PVC WHT
9985 0091000	1,000 FT	2.000 LB	WHITE	P	26 STR PVC WHT
9985 010100	100 FT	0.200 LB	BLACK		26 STR PVC BLK
9985 0101000	1,000 FT	2.000 LB	BLACK	P	26 STR PVC BLK
9985 013100	100 FT	0.200 LB	BLUE, DARK		26 STR PVC DK.BLU
9985 0131000	1,000 FT	2.000 LB	BLUE, DARK	P	26 STR PVC DK.BLU

Notes:

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 08-16-2013

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sales believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its bublication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2