Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



A0270168 Connectivity Accessories - DISTRIBUTION RING







For more Information please call

1-800-Belden1

General Description:

DISTRIBUTION RING

Usage (Overall)

Suitable Applications: IBDN System 1200, Telecom Room

Related Parts: BIX Termination Kit

Physical Characteristics (Connectivity)

Dimensions

Dimensions

Height (in.) Width (in.) Depth (in.) 3.000 6.850 1.210

Materials

Materials:

Description Material Ring Plastic - UL94V-0

Color

Color: Beige

Weight

Weight: 0.110 lbs.

Packaging

Packaging: Individually packaged in a clear plastic bag.

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

Safety Listing: ACA, Bi-national Standard Listed

Suitability

Suitability - Indoor: Yes - Indoor

Notes (Overall)

Product Family

Put Ups and Colors:

Item	n #	Putup	Ship Weight	Color	Notes	Item Desc
A02	270168	1 EA	0.156 LB			DISTRIBUTION RING

Revision Number: 0 Revision Date: 03-23-2012

© 2017 Belden, Inc

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Page 1 of 1