

A0410473 Cable Assemblies - CAT5 BIX Patch Cord



For more Information
please call

1-800-Belden1



General Description:

CAT5 BIX Patch Cord, 1 Pair, 24 AWG Stranded, CMR, Grey, 10 ft. (3.0 m).

Usage (Overall)

Suitable Applications:	TIA Category 5
Related Parts:	Bix Connector - QCBIX1A/1A4 connector

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
1	24	Stranded	BC - Bare Copper

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Color Code Chart:

Color
Grey

Overall Diameter

Overall Nominal Diameter:	3.048 mm
---------------------------	----------

Physical Characteristics (Connectivity)

Materials

Materials:

Description	Type	Material
BIX		Polymer
Boot		PVC
Front Connection	Blades	Phosphor Bronze with Tin Plating over Nickel

Color

Boot Color:	Greyameleon
-------------	-------------

Weight

Weight:	0.043 kg
---------	----------

Packaging

Packaging:	Individually packaged in a clear plastic bag.
------------	---

Mechanical Characteristics (Connectivity)

Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C
Operating Temperature Range:	-10°C To +60°C
Min. Bend Radius (Overall Cable):	26.416 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	Riser
Other Standards:	Category 5

A0410473 Cable Assemblies - CAT5 BIX Patch Cord

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
MII Order #39 (China RoHS):	EUP 50
Telecommunications Standards:	Category 5 - TIA 568.B.2
Safety Listing:	ACA, Bi-national Standard Listed

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Transmission Characteristics (Connectivity)

Performance Table - Footnote:	100 Meter Cable Specifications - * TIA-EIA-568-B.2 Category 5 Standard ----- PSACRF is formally PSELFEXT
Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute
Current Rating:	1,500 A
Insulation Resistance:	500 M-Ohm Minimum
Max. Contact Resistance:	20 m-Ohm

Notes (Overall)

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
A0410473	1 EA	2.337 LB			BIX PATCH CORD,

Revision Number: 0 Revision Date: 05-13-2010

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.