

+ RELAYS, CONTACTORS & SWITCHES

#### **TOGGLE SWITCHES**



✓ Active

# TE CONNECTIVITY (TE) A203KZQ04

Alcoswitch | A

1825139-1

TE Internal Number: 1825139-1

Alias ID: A203KZQ04

#### **EU RoHS Compliant with Exemptions EU ELV Compliant with Exemptions**

Configuration (Pole-Throw) Double Pole - Double Throw

**Bushing Thread Size** 1/4-40 UNS-2A

Sealed Yes

**Contact Base Material** Copper

**Contact Plating** Silver



#### **PRODUCT DRAWING**

## **DOCUMENTATION**

**Product Drawings** 

### **GEMINI A SERIES TOGGLE SWITCH, DOUBLE POLE,3 POS FUNCTIONS(03,05,07,11,13&15)**

PDF

**English** 

Catalog Pages/Data Sheets

### SWITCHES\_CORE\_PROGRAM\_CATALOG

PDF

**English** 

## **GEMINI\_SERIES\_SWITCHES\_QUICK\_REF\_GUIDE\_2-1773458-5**

PDF

**English** 

**FEATURES** 

+

Please review product documents or contact us for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

**Product Type Features** 

Sealed Yes
Toggle Style Locking

Switch Type Toggle

**Product Type** Switch

**Toggle Actuation** Vertical

**Configuration Features** 

**Configuration (Pole-Throw)** Double Pole - Double Throw **Operating Function** On Off On

**Electrical Characteristics** 

Contact Resistance (m $\Omega$ ) 10 Voltage Rating 125 VAC, 28 VDC Insulation Resistance (M $\Omega$ ) 1000 Dielectric Strength (VAC) 1000

**Body Features** 

Bushing Thread Size 1/4-40 UNS-2A Seal Type Terminal Seal (Epoxy) Bushing Style Unthreaded Actuator Finish Nickel

**Contact Features** 

Contact Base Material Copper Contact Plating Silver Contact Current Rating (A) 5

**Termination Features** 

**Termination Type** Wire Lugs

Mechanical Attachment

**Mounting Type** Solder

**Housing Features** 

**Process Sealed No** 

**Dimensions** 

**Bushing Length (in)** .28

Toggle Length 16.28 mm [.641 in]

Industry Standards	
UL Flammability Rating UL 94V-1	
PRODUCT COMPLIANCE	+

Statement of Compliance

# **Statement of Compliance**

PDF