


Style A with leads



Style S with lugs



Sec.	STANCOR PART NUMBER	Style	Impedance (Ohms)		Power Steps (Watts)	D.C. Resist		Overall Turns Ratio	Frequency Response (Hz) ±3 DB	RMS Test Voltage	Termination		DIMENSIONS-INCHES				Weight (lbs.)	Agency Certif.	
			Pri.	Sec.		Pri. Ohms	Sec. Ohms				Pri.	Sec.	H	W	D	MW			MD
<b>25 Volt Line to Voice Coil</b>																			
A	A-8099	A	312/625/1250	4/8	2/1/0.5	75	0.6	12.2:1	50-15000	1000	Lugs	Lugs	1.25	2.12	1.38	1.75	-	0.30	-
	A-8095	A	125/250/500/1000/2000	4/8	5/2.5/1.25/.62/.31	100	0.6	15.6:1	30-20000	1000	Lugs	Lugs	1.38	2.38	1.50	2.00	-	0.40	-
	A-8096	S	78/156/312/625/1250	4/8/16	8/4/2/1/0.5	72	1.0	8.8:1	30-20000	1000	Lugs	Lugs	2.00	2.38	1.62	2.00	-	0.65	-
<b>70.7 Volt Line to Voice Coil</b>																			
B	A-8084	A	1250/2500/5000/10000/20000/40000	8	4/2/1/.5/.25/.12	1150	0.4	67.6:1	50-20000	1000	Leads	Leads	1.63	2.88	1.75	2.38	-	0.70	-
	A-8105	A	1000/2000/4000/8000/16000	4/8	5/2.5/1.25/.62/.31	950	0.6	44.2:1	50-20000	1000	Lugs	Lugs	1.38	2.38	1.50	2.00	-	0.40	-
	A-8102	S	625/1250/2500/5000/100000	4/8/16	8/4/2/1/0.5	670	1.0	24.9:1	50-20000	1000	Lugs	Lugs	2.00	2.38	1.62	2.00	-	0.70	-
C	A-8081	S	500/555/625/715/833	8/16	10/9/8/7/6	70	1.3	6.86:1	50-20000	1000	Lugs	Lugs	2.00	2.38	1.62	2.00	-	0.70	-
	A-8103	S	312/625/1250/2500/5000/100000	4/8/16	16/8/4/2/1/0.5	585	1.1	24.5:1	40-15000	1000	Lugs	Lugs	2.75	3.13	2.25	2.81	-	1.50	-
	A-8078	S	167/250/500/1000	4/8/16	30/20/10/5	35	0.8	8:1	40-20000	1000	Lugs	Lugs	2.38	2.88	1.75	2.38	-	1.00	-
	A-8079	S	100/125/200/333	4/8/16	50/40/25/15	22	1.2	4.46:1	40-20000	1000	Lugs	Lugs	2.38	2.88	2.00	2.38	-	1.40	-

For outline drawings refer to page 62.

Interstage: Single Plate (7,000 to 15,000) to Push-Pull Grids

Sec.	STANCOR PART NUMBER	Style	Ratio	Max. Pri. DCMA	Termination		D.C. Resist		Overall Turns Ratio	Frequency Response (Hz) ±3 DB	RMS Test Voltage	DIMENSIONS-INCHES				Weight (lbs.)	Agency Certif.	
					Pri.	Sec.	Pri. Ohms	Sec. Ohms				H	W	D	MW			MD
D	A-52C	A	1:2	10	Leads	Leads	570	1450	1:2	100-10000	1000	1.38	2.38	1.50	2.00	-	0.4	-
	A-53C	A	1:3	10	Leads	Leads	400	1500	1:3	100-10000	1000	1.38	2.38	1.50	2.00	-	0.5	-

