



Main

| | |
|--------------------------------|--------------------------|
| Range of product | Acti9 |
| Product name | Acti9 iCT |
| Product or component type | Contacteur |
| Device short name | ICT |
| Device application | Lighting |
| Poles | 3P + N |
| [Ie] rated operational current | 63 A AC-7A 20 A AC-7B |
| Pole contact composition | 4 NO |
| Network type | AC |
| Control type | Remote control |
| [Uc] control circuit voltage | 230...240 V AC 50 Hz |

Complementary

| | |
|--|------------------------------|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50 Hz |
| Maximum power | 2.1 W at 220...240 V AC |
| [Ui] rated insulation voltage | 440 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Control signal type | Maintained |
| Switching frequency | 100 switching operations/day |
| Local signalling | Action indicator |
| Hold-in power consumption in VA | 6.5 VA |
| Inrush power in VA | 53 VA |
| Mounting mode | Clip-on |
| Mounting support | 35 mm symmetrical DIN rail |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------|--|
| 9 mm pitches | 6 |
| Height | 85 mm |
| Width | 54 mm |
| Depth | 60 mm |
| Colour | White |
| Mechanical durability | 1000000 cycles |
| Electrical durability | 100000 cycles IEC/EN 61095 63 A 50 Hz AC-7A 30000 cycles IEC/EN 61095 20 A 50 Hz AC-7B 30000 cycles IEC/EN 61095 50 Hz AC-7C 100000 cycles EN/IEC 60947-4-1 50 Hz AC-1 30000 cycles EN/IEC 60947-4-1 50 Hz AC-3 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5a 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5b |
| Technology type | Desynchronized neutral pole |
| Condition of use | LED lighting should be controlled as a group |
| Connections - terminals | Control circuit: tunnel type terminals2 cable(s) 1.5 mm ² rigid Control circuit: tunnel type terminals1 cable(s) 1.5...2.5 mm ² rigid Power circuit: tunnel type terminals1 cable(s) 6...16 mm ² flexible Power circuit: tunnel type terminals1 cable(s) 6...25 mm ² rigid Control circuit: tunnel type terminals2 cable(s) 1.5...2.5 mm ² flexible |
| Tightening torque | Control circuit: 0.8 N.m Power circuit: 3.5 N.m |
| Product compatibility | IACTs IATet IACTc IACTp |
| Compatibility code | ICT |
| Market segment | Small commercial Residential |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC/EN 61095 |
| Noise level | 30 dB |
| Heat dissipation | 2.1 W at 50/60 Hz |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 2 |
| Tropicalisation | 2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095 |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 363 g |
| Package 1 Height | 6 cm |
| Package 1 width | 11.1 cm |
| Package 1 Length | 12.2 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 4 |
| Package 2 Weight | 1.53 kg |
| Package 2 Height | 13 cm |
| Package 2 width | 12 cm |

| | |
|------------------------------|----------|
| Package 2 Length | 25 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 24 |
| Package 3 Weight | 9.674 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |