



Main

| | |
|---------------------------|---|
| Range of product | Phaseo Optimum |
| Product or component type | Safety and isolation transformer |
| Rated power in VA | 100 VA |
| Input voltage | 230 V AC single phase , terminal(s): N-L1 400 V AC phase to phase , terminal(s): L1-L2 |
| Output voltage | 24 V AC |
| Secondary winding | Single |
| Protective cover | Without |

Complementary

| | |
|------------------------------|---|
| Input voltage limits | 207...253 V 360...440 V |
| Network frequency limits | 47...63 Hz |
| Input voltage tolerance | +/- 15 V |
| Efficiency | 86 % |
| Power dissipation in W | 16.3 W |
| Output sustained overvoltage | 9 % (no load, hot state) |
| Voltage drop at rated load | 0 % |
| No load losses | 7.1 W |
| Short-circuit voltage | 7.86 % |
| Output protection type | Against overload , protection technology: external Against overvoltage , protection technology: external Against short-circuits , protection technology: external |
| Connections - terminals | Screw type terminals for input connection , connection capacity: 5 x 4 mm ² AWG gauge11 Screw type terminals for input ground connection , connection capacity: 1 x 4 mm ² AWG gauge11 Screw type terminals for output connection , connection capacity: 2 x 4 mm ² AWG gauge11 |
| Marking | CE |
| Fixing mode | By 4 screws , screw(s) # = 4.8 mm on vertical panel , operating position: vertical By 4 screws , screw(s) # = 4.8 mm on vertical panel , operating position: horizontal By 4 screws , screw(s) # = 4.8 mm on horizontal panel with derating to 90 % By clips (with mounting plate) on 35 mm symmetrical DIN rail |
| Electrical insulation class | Class B |
| Product weight | 2.1 kg |

Environment

| | |
|--|---|
| Product certifications | UR |
| IP degree of protection | IP20 conforming to EN/IEC 60529 |
| Protective treatment | TC |
| Ambient air temperature for operation | -20...50 °C |
| Ambient air temperature for storage | -40...80 °C |
| Class of protection against electric shock | Class I conforming to VDE 0106-1 |
| Dielectric strength | 2000 V between winding and ground 4000 V between primary and secondary |
| RoHS EUR conformity date | 0623 |
| RoHS EUR status | Compliant |