



**Distribution Compression Splice**

**T&B Catalog Number:**

ACJ205

**UPC Number:**

78378685541

**Status:**

Active

**Description:**

Aluminum 4-3/4 inch Partial-Tension Distribution Compression Splice for Wire Range: 2/0(7,19), Mechanical Dies: BY41, W-245, 635, Hydraulic Dies: B30EA, 245, 5/8-1, 635

**Features**

- Center stop ensures proper conductor positioning.
- Prefilled with Oxide Inhibitor.
- Plastic end plugs remove easily.
- Standards compliant. Meets ANSI C119.4 requirements for 40 percent partial-tension.

**General**

Style	Partial-Tension
Material	Aluminum
Wire Size	2/0(7,19)
EEI Classification	9A

**Dimension Information**

Length (inches)	4 3/4
-----------------	-------

**Tooling**

Mechanical Tool OD58 Dies	BY41
Mechanical Tool OD58 Crimps Per End	4
Mechanical Tool MD Series Dies	W-245
Mechanical Tool MD Series Crimps Per End	4
Mechanical Tool O-52 Dies	635
Mechanical Tool O-52 Crimps Per End	4
Hydraulic Tool JB12B Dies	B30EA
Hydraulic Tool JB12B Crimps Per End	2
Hydraulic Tool Y Series Dies	245
Hydraulic Tool Y Series Crimps Per End	2
Hydraulic Tool WH Series Dies	5/8-1, 635
Hydraulic Tool WH Series Crimps Per End	4, 2
End	

**Packaging**

T&B Inner Pack	25
Package in Units	250
T&B Sold in UOM	Each
T&B Weight Per UOM	11.18 lbs. per 100

**Notes**

- Use with all-aluminum conductor.
- OD58 Dies are interchangeable with those listed for O-52.

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)