

RECPT, 24 SZ 18 SOC, RD, WIDE THD

AHDM04-24-18SR

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

SHELL: ZINC ALLOY, NICKEL PLATED

INSERT AND RETAINING RING: THERMOPLASTIC

SEAL: SILICONE RUBBER


2. MODIFICATIONS: THREADED HOUSING; REDUCED DIA. WIRE SEAL

3. SPECIFICATIONS:


- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2
- MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC. 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25℃.
- 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDM06-24-18P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

$\sqrt{6}$ CONTACT SIZE AND WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
8	3.43 mm (.135 in)	5.59 mm (.220 in)	8-10 AWG	60 AMPS
12	2.46 mm (.097 in)	4.01 mm (.158 in)	10-14 AWG	25 AMPS
16	1.35 mm (.053 in)	3.05 mm (.120 in)	14-20 AWG	13 AMPS



1 11/16-18 UNEF 2A THREAD



-M38X1.5 6g THREAD

	AHDM04-24-18SR		R									
	PART NUMBER			DESCRIPTION					ITEM			
QUANTITY MATERIALS LIST												
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.16 3) Note reference = X		SIGNATURES		S DATE	Amphopol							
		DRAWN: BROOK		24/OCT/18	Amphenol							
		CHECKED:	ORION	24/OCT/18	Sine Systems - www.amphenol-sine.com		1	_				
		ENGINEER:					44724 Morley Drive Clinton Township, MI 48	036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	24/OCT/18	_		Clinton Township, Wi 46	030				
		CUSTOMER:			RECPT. 24 SZ 18 SOC. RD. WIDE THD							
PROCESS SPECIFICATIONS:		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL			Туре	DWG NO:	,					
				size R	C-	AHDM04-24	1-18SR	,	EVISION Δ2			
						/ u IDINIOT L			· · · _			
NEXT ASS'Y:				SCALE: N	ONE		SHEET 1	OF	1			