



Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 1 Mohm(min)
 4. dielectric test: DC 300V

PIN ASSIGNMENT		
P1		P2
1	RED	1
2	WHITE	2
3	S	3

5		OUTER MODEL PVC 45P COLOR BLACK		4.8	g
4		ROUND TIN OD1.0mm		0.15	g
3		3.5 STEREO JACK OD8.0mm		1	P2
2		3.5 STEREO PLUG PLATE NICKEL L=30mm		1	P1
1		T.C (7/0.12*2C+43/0.12)*1C (RED,WHITE)ø3.0 COLOR BLACK(CS-001)	01	1	1500mm
NO.	PART NO.	DESCRIPTION	VENDER	QTY	UNIT/REF



ITEM NO **AK-AV100-R (1.50 M)**

TITLE **Stereo Connection Cable,
3-Pin 3.5mm Stereo Male to 3.5mm Stereo Male**

ASSMANN
 Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
 Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 © Copyright 2008 by Assmann Electronic Components
 All International Rights Reserved