



Notes:

- Cable: UL2725 80°C 30V[26AWG(1/0.404)*2F +AL/MY+Drain Wire(1/0.32*2)]TIN INS: Foam-PE OD: $\varnothing 1.1 \pm 0.05$ mm PVC Jacket OD: $\varnothing (2.2 \pm 0.1) * (7.8 \pm 0.2)$ mm Color: Red(Pantone 200C) Print: 2725 E209329 AWM 80°C 30V VW-1 Serial ATA 26AWG Lian Feng(Black Word) Impedance: 100 ± 5 OHM(Supplier: Lian Feng)
- Connector: 2-1 Material: Housing: High Temperature Polyester & Glass Fiber UL 94V-0 Terminal: Copper Alloy
2-1 Plating: Contact Area: 15u" Gold Plated
- Hood: Molded Type, PVC 45P, Color: Black(NK-K01)
- Cable Ass'y Electrical Test: 4-1: 100% Open Short & MIS Wire Test
4-2: Contact Resistance 20M OHM Min
4-3: Insulation Resistance 20M OHM Min
- Packing: See P-0039 Rev. C Packing Drawing
(Binding Size must be smaller than Blister)

| DWG | P/N | L(mm) | T(mm) | EAN Code | Blister |
|------------|---------------|-------|-------|---------------|---------|
| 140-0497-4 | AK-SATA-030-R | 300 | 10 | 4016032152712 | DB VP2 |
| 140-0497-3 | AK-SATA-075-R | 750 | 20 | 4016032121695 | DB VP2 |
| 140-0497-2 | AK-SATA-100-R | 1000 | 20 | 4016032121138 | DB VP2 |
| 140-0497-1 | AK-SATA-050-R | 500 | 10 | 4016032121121 | DB VP2 |



ITEM NO
AK-SATA-XXX-R

TITLE
 Serial ATA 150 Connector Cable,
 7-Wire Cable, UL21149

ASSMANN
 Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
 Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 © Copyright 2008 by Assmann Electronic Components
 All International Rights Reserved