

	1	2	3	4	5	6	7																																																																
A								A																																																															
B								B																																																															
C								C																																																															
D	<p>② TOLERANCE</p> <table border="1"> <thead> <tr> <th>Length(meter)</th> <th>Max-M</th> <th>Min-M</th> </tr> </thead> <tbody> <tr><td>0.3</td><td>+0.03</td><td>-0.025</td></tr> <tr><td>0.5</td><td>+0.03</td><td>-0.025</td></tr> <tr><td>1</td><td>+0.04</td><td>-0.035</td></tr> <tr><td>2</td><td>+0.06</td><td>-0.06</td></tr> <tr><td>3</td><td>+0.09</td><td>-0.09</td></tr> <tr><td>5</td><td>+0.15</td><td>-0.15</td></tr> <tr><td>7</td><td>+0.21</td><td>-0.21</td></tr> <tr><td>10</td><td>+0.3</td><td>-0.3</td></tr> <tr><td>15</td><td>+0.45</td><td>-0.45</td></tr> <tr><td>20</td><td>+0.6</td><td>-0.6</td></tr> <tr><td>30</td><td>+0.9</td><td>-0.9</td></tr> </tbody> </table>							Length(meter)	Max-M	Min-M	0.3	+0.03	-0.025	0.5	+0.03	-0.025	1	+0.04	-0.035	2	+0.06	-0.06	3	+0.09	-0.09	5	+0.15	-0.15	7	+0.21	-0.21	10	+0.3	-0.3	15	+0.45	-0.45	20	+0.6	-0.6	30	+0.9	-0.9	D																											
Length(meter)	Max-M	Min-M																																																																					
0.3	+0.03	-0.025																																																																					
0.5	+0.03	-0.025																																																																					
1	+0.04	-0.035																																																																					
2	+0.06	-0.06																																																																					
3	+0.09	-0.09																																																																					
5	+0.15	-0.15																																																																					
7	+0.21	-0.21																																																																					
10	+0.3	-0.3																																																																					
15	+0.45	-0.45																																																																					
20	+0.6	-0.6																																																																					
30	+0.9	-0.9																																																																					
E	<p>PIN ASSIGNMENT</p>							E																																																															
F	<p>Order Code:</p> <p>① A-MCSP-80XXX : color Grey</p> <p>④② Order lengths in meter: 0.3,0.5,1,2,3,5,7,10,15,20,30</p> <p>A-MCSP-80XXXX</p> <p>④② Order lengths in meter: 0.3,0.5,1,2,3,5,7,10,15,20,30</p> <p>Order color:(R)Red,(Y)Yellow (G)Green,(B)Blue</p>							F																																																															
G	<p>RoHS compliant</p> <p>Unit:: mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>FREE</th> <th>⑥</th> <th>⑦</th> <th>23.08.2018</th> <th>Segal</th> <th>Date</th> <th>Name</th> <th>Customer-No.</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>±X</td> <td>③</td> <td>Add "CATSE"</td> <td>20.10.2017</td> <td>Stephon</td> <td>26.06.2015</td> <td>Joanna</td> <td>ASSMANN WSW-No.</td> </tr> <tr> <td>X.X</td> <td>±X</td> <td>④</td> <td>Add length for 20M and 30M</td> <td>20.09.2017</td> <td>Fred</td> <td>23.08.2018</td> <td>Amy</td> <td>A-MCSP-80XXXX</td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td>③</td> <td>remove mark on the mould</td> <td>29.06.2016</td> <td>Joanna</td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>②</td> <td>Add length for 300mm</td> <td>18.05.2015</td> <td>Joanna</td> <td></td> <td></td> <td>Drawing-No.</td> </tr> <tr> <td>ANGLE</td> <td>±X°</td> <td>①</td> <td>Add P/N and change tolerance</td> <td>15.02.2015</td> <td>Joanna</td> <td></td> <td></td> <td>ASS 7425 CA</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td></td> <td></td> <td></td> <td></td> <td>Replace</td> </tr> </tbody> </table>							Scale	FREE	⑥	⑦	23.08.2018	Segal	Date	Name	Customer-No.	TOLERANCE	±X	③	Add "CATSE"	20.10.2017	Stephon	26.06.2015	Joanna	ASSMANN WSW-No.	X.X	±X	④	Add length for 20M and 30M	20.09.2017	Fred	23.08.2018	Amy	A-MCSP-80XXXX	X.XX	±X	③	remove mark on the mould	29.06.2016	Joanna				DIM	TOL	②	Add length for 300mm	18.05.2015	Joanna			Drawing-No.	ANGLE	±X°	①	Add P/N and change tolerance	15.02.2015	Joanna			ASS 7425 CA	Angle	TOL	Id.	Modification					Replace	G
Scale	FREE	⑥	⑦	23.08.2018	Segal	Date	Name	Customer-No.																																																															
TOLERANCE	±X	③	Add "CATSE"	20.10.2017	Stephon	26.06.2015	Joanna	ASSMANN WSW-No.																																																															
X.X	±X	④	Add length for 20M and 30M	20.09.2017	Fred	23.08.2018	Amy	A-MCSP-80XXXX																																																															
X.XX	±X	③	remove mark on the mould	29.06.2016	Joanna																																																																		
DIM	TOL	②	Add length for 300mm	18.05.2015	Joanna			Drawing-No.																																																															
ANGLE	±X°	①	Add P/N and change tolerance	15.02.2015	Joanna			ASS 7425 CA																																																															
Angle	TOL	Id.	Modification					Replace																																																															
H	<table border="1"> <thead> <tr> <th>NO</th> <th>PART NO</th> <th>DESCRIPTION</th> <th>QTY</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>3</td> <td>mold</td> <td>PVC,50P</td> <td>9.0</td> <td>G</td> </tr> <tr> <td>2</td> <td>plug</td> <td>8P8C plating gold 3U" with metal shield</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>1</td> <td>cable</td> <td>FTP (26AWG*(P)*4+D+A+PVC, OD:5.2±0.2mm CAT5E</td> <td>2.0</td> <td>M</td> </tr> </tbody> </table> <p>Electrical 100% short open, miswire test</p>							NO	PART NO	DESCRIPTION	QTY	UNIT	3	mold	PVC,50P	9.0	G	2	plug	8P8C plating gold 3U" with metal shield	2	PCS	1	cable	FTP (26AWG*(P)*4+D+A+PVC, OD:5.2±0.2mm CAT5E	2.0	M	H																																											
NO	PART NO	DESCRIPTION	QTY	UNIT																																																																			
3	mold	PVC,50P	9.0	G																																																																			
2	plug	8P8C plating gold 3U" with metal shield	2	PCS																																																																			
1	cable	FTP (26AWG*(P)*4+D+A+PVC, OD:5.2±0.2mm CAT5E	2.0	M																																																																			
<p>ASSMANN components</p>																																																																							
<p>ASS 7425 CA rev06</p>																																																																							
<p>Sheet</p>																																																																							