



WIRE	CAT.6 PIMF STR 26AWG
PLUG	YUS-06 8P8C 50u"
LENGTH	/

Conductor	Bare Copper 26AWG 7/0.16 ± 0.015mm
Insulation	Thickness: MIN at any point: 0.2mm MAX AVG: 0.35mm Diameter: 1.05 ± 0.06mm
Jacketing	PVC Thickness: MIN at any point: 0.50mm MAX AVG: 0.60mm Diameter: 6.1 ± 0.2mm

A-MCSSP60XXX/X-R

Length	Color
005 0.5 Meters	- Gray
010 1.0 Meters	/R Red
020 2.0 Meters	/B Blue
030 3.0 Meters	/Y Yellow
050 5.0 Meters	/G Green
070 7.0 Meters	
100 10.0 Meters	
150 15.0 Meters	
200 20.0 Meters	

PINOUT

PA/R	P1(T568B)	WIRE	P2(T568B)
1	1	WHT/ORG	1
	2	ORG	2
2	3	WHT/GRN	3
	6	GRN	6
3	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved

RoHS
Compliant

ITEM NO
A-MCSSP60XXX/X-R

TITLE
CAT 6 SFTP Patch Cable