



HOME ABOUT US INDUSTRIES PRODUCTS & APPLICATIONS NEWS & EVENTS CONTACT & SUPPORT

Speed, Position
& Current

Thermal

Pressure,
Force & Flow

Relays

Switches &
Equipment Health

Potentiometers
& Resistors

Safety
Products

Vehicle Cont
& Monitoring

Honeywell Sensing and Control


Where to buy ?

Interactive
Catalog Home

Product Family
Information

Specification
Search

Search
Help



Representative photograph,
actual product appearance
may vary.

Click here for a print friendly version of this datasheet.

AML27ABK2AA23BA

AML27 Series, Electronic Control Keylock, Square, Key Entry,
Unlighted, SPDT, Maintained, Snap in panel mount

Features

2 or 3 positions, maintained, (90° throw) and momentary action, (60° throw).

5-bit key combinations

UL recognized, CSA certified.

Static discharge protection (up to 20 kV when grounded).

Typical Applications

Enable control of access to computer peripherals, keyboards, point-of-sale terminals, and secu systems which are locked when unattended; and other locations where tampering must be disc

- ▣ Dimensions
- ▣ Terminal
Dimensions
- ▣ Accessories
- ▣ Specifications
- ▣ [Engineering
Drawings On-Line](#)

Product Specifications	
Product Type	Electronic Control Keylock
Housing Type	Square
Circuitry	SPDT
Action	Maintained
Mounting	Snap-in Panel
Lamp Type	Unlighted
Termination	.110 x .020 (Solder or Quick-Connect)
Ampere/Voltage Range (Resistive Load)	0.4-2 A @ 0.5 -250 Vac, 0.4-2 A @ 0.5-30 Vdc, 0.4-2 A @ 0.5-125 Vac
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Series Name	AML27 Series

*Due to regional agency approval requirements, some products may not be available in your area.
Please contact your regional Honeywell office regarding your product of choice.*