



Specifications:

Material:
 Housing: Poly Carbonate(PC) UL94V-2
 Contact: Phosphor Bronze
 Plating: 6u" gold plated
 100u" Nickel under plated
 Shell: High strength copper alloy with Nickel plated
 Operating temperature: -40°C to +125°C

Electrical:
 Current rating: 250V AC max. at 2A
 Dielectric: 500V AC
 Insulation resistance: 500MΩ
 Termination resistance: 35MΩ max
 after environmental tests
 Tensile strength: 20 LBS (89N) min.
 Durability: 500 mating cycles

Complies with FCC68/F
 ② Wire gauge: 30AWG-24AWG Solid wire
 Cable OD size: round cable 3.0~5.5mm
 Wire size: 0.95±0.05mm

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	29.04.2016	Amy
X.X	±0.20					Approved	03.04.2019	Amy
X.XX	±0.10							
X.XXX	±0.05	②	Add cable wire size information	03.04.2019	Amy			
DIM	TOL	①	Update the drawing	12.06.2016	Amy			
Angle	±2°	①	Drawn	29.04.2016	Amy			
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet	

A-MO 8/8-SRS

Drawing-No. **ASS 7232 CO** rev02