	REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	26DEC13	DRP			
A4	C0540S	UPDATE DIMENSIONS	28JUN16	JONY	TOMMY		
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY		
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	то		

TITLE


PLUG, 3 SOCKET, AT SERIES

DWG NO:


AT06-3S-XXX

REV: A5

SH



REQUIRES CONTACT RETENTION WEDGE AW3S



CAVITY "B" CAVITY "A" CAVITY "A"

CAVITY "C"



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	SEE PART NUMBER CHART			REF: DT06-3S, DT06-3S-E004, DT06-3S-P012				1
	PART NUMBER				DE	SCRIPTION		ITEM] -
QUANTITY		MATERIALS LIST			┣				
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.08 3 PL DEC ±0.08		SIGN	ATURES	DATE	^	mpho	no	1	1
		DRAWN:	LOUIE	23NOV20		mphe		I	
		CHECKED:	ORION	24NOV20	Sine Systems - www.amphenol-sine.com				
3) Note reference	- <u>x</u>	ENGINEER:				44724 Morley Drive			
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	25NOV20		Clinton Township, MI 480	136		-
		CUSTOMER:			PI	UG. 3 SOCKET. AT	SERIES		
PROCESS SPECIFICATIONS:		INFORMATION SPECIFICATION SHOWN HERE THE AMPHENO	S IS SUPPLIED F ONLY. DESIGN NS AND PERFOR ON ARE THE PR OL CORPORATIO	FEATURES, RMANCE DATA OPERTY OF DN. NO RIGHTS		DWG NO: AT06-3S-			-
NEXT ASS'Y:		OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		SCALE: NONE		SHEET 1	∧ ₀ 1		

PART NUMBER CHART		
COLOR	PART NUMBER	
GREY	AT06-3S	
BLACK	AT06-3S-BLK	
BLUE	AT06-3S-BLU	
BROWN	AT06-3S-BRN	
GREEN	AT06-3S-GRN	
RED	AT06-3S-RED	
WHITE	AT06-3S-WHT	
YELLOW	AT06-3S-YEL	
ORANGE	AT06-3S-ORG	



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: N/A

3. SPECIFICATIONS:

- 3.1 CURRENT RATING: 13 AMPS
- 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
- 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2
- MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
- 3.5 MOISTURE RESISTANCE: IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)
 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-3P* RECEPTACLE (* = MODIFICATIONS AND COLORS)

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6\CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	2.24 mm	3.68 mm	14 - 20 AWG
10	(.088 in)	(.145 in)	(2.0-0.5mm ²)

AT Series[™] - Contact Size 16 Options

Machined Contacts, Sockets & Pins						
Part Number Description		Size	AWG	Туре		
AT60-215-1631	Male Contact - Pin, Gold-plated	Male Contact - Pin, Gold-plated 16 14		Machined		
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined		
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined		
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined		
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined		
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined		
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined		
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined		
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined		
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined		
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined		
AT62-201-16141-22	Female Contact - Socket, Nickel-plated 16 22-24 Mach		Machined			

	Tooling - Machined Contacts				
Part	Part Part Number Description				
\leq	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)			
37	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)			

Contact Removal Tools				
Part	Part Number	Description		
	ATRT-100	Used for removal of contacts for A Series™ products		
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16		

	Sealing Plugs				
Part	Part Part Number Description				
	A114017	Sealing Plug, Size 16, White			
	A114017-SR	Sealing Plug, Size 16, SR01 Series, Black			
	AT13-217-1605	Locking Sealing Plug, Size 16, Grey			
	AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red			

	Stamped & Formed Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре		
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed		
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed		
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed		
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed		
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed		
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed		
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed		
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed		
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed		
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed		
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed		
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed		
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed		
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed		
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed		
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number Description				
-	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)			
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)			
A State	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)			
No.	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)			
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)			
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)			
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 03/2022