





1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


2. MODIFICATIONS: N/A

- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE:


IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION)

IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-4P\* RECEPTACLE (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.





CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
4.0	2.24 mm	3.68 mm	14 - 20 AWG	
16	(.088 in)	(.145 in)	(2.0-0.5mm²)	



PART NUMBER CHART		
COLOR PART NUMBER		
GREY	AT06-4S	
BLACK	AT06-4S-BLK	
BLUE	AT06-4S-BLU	
BROWN	AT06-4S-BRN	
GREEN	AT06-4S-GRN	
RED	AT06-4S-RED	
WHITE	AT06-4S-WHT	
YELLOW	AT06-4S-YEL	
ORANGE	AT06-4S-ORG	

	REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	26DEC13	DRP			
A4	C0540S	UPDATE DIMENSIONS	22JUN16	JONY	TOMMY		
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY		





STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	PART NUMBER CHART			REF: DT06-4S, DT06-4S-E004, DT06-4S-P012	
	PART N	NUMBER	1	DESCRIPTION		
QUANTITY		- 1	MAT	ERI	ALS LIST	
	WISE SPECIFIED	SIGN	IATURES	DATE	Amphonol	
All dimensions a     Tolerances are a     PL DEC ±0.30		DRAWN:	LOUIE	23NOV20	Amphenol	
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	25NOV20	Sine Systems - www.amphenol-sine.com	_
3) Note reference	<b>-</b> 🗴	ENGINEER:			44724 Morley Drive	
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20	V20 Clinton Township, MI 48036	
		CUSTOMER:			PLUG, 4 SOCKET, AT SERIES	
			G IS SUPPLIED I			
PROCESS SPECIFICA	ROCESS SPECIFICATIONS:  SPECIFICATIONS AND PERFORM SHOWN HEREON ARE THE PRO THE AMPHENOL COPPORATION OF REPRODUCTION ARE IMPLIE DIMENSIONS ARE SILIFICATION OF REPRODUCTION ARE IMPLIE DIMENSIONS ARE SILIFICATION.		RMANCE DATA ROPERTY OF DN. NO RIGHTS LIED. ALL	- ATOM 40 VAVA	15 15	
NEXT ASS'Y:			RING VARIATION			1

DWG NO:

PLUG, 4 SOCKET, AT SERIES

AT06-4S-XXX

REV: **A5** SH: 1

## **AT Series™** - Contact Size 16 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Type	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated 16 16-20 Mac		Machined		
AT62-201-1631	Female Contact - Socket, Gold-plated 16 16-20 Mac		Machined		
AT60-202-16141	Male Contact - Pin, Nickel-plated 16 16-20 Mach		Machined		
AT62-201-16141	Female Contact - Socket, Nickel-plated 16 16-20		Machined		
AT60-202-1631-22	Male Contact - Pin, Gold-plated 16 22-24 N		Machined		
AT62-201-1631-22	Female Contact - Socket, Gold-plated 16 22-24 Mach		Machined		
AT60-202-16141-22	Male Contact - Pin, Nickel-plated 16 22-24 Machin		Machined		
AT62-201-16141-22	Female Contact - Socket, Nickel-plated 16 22-24 Machined		Machined		

Tooling - Machined Contacts			
Part	Part Number	Description	
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)	
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)	

Contact Removal Tools			
Part	art Part Number Description		
	ATRT-100	Used for removal of contacts for A Series™ products	
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16	

Sealing Plugs			
Part	Part Number	Description	
	A114017	Sealing Plug, Size 16, White	
	A114017-SR	Sealing Plug, Size 16, SR01 Series, Black	
	AT13-217-1605	Locking Sealing Plug, Size 16, Grey	
	AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red	

Stamped & Formed Contacts, Sockets & Pins					
Part Number	r Description		AWG	Туре	
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed	
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed	
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed	
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed	
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed	
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed	
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed	
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed	
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed	
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed	
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed	
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed	
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed	
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed	
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed	
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed	

Tooling - Stamped & Formed Contacts			
Part	Part Number Description		
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)	
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)	
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)	
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)	
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)	
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)	
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)	

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 03/2022