

TITLE:	BOOT,ATM, 2 WAY,PLUG	DWG NO:	ATM2S-BT-XX	REV: A1	SH: 1	OF: 1

	REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR			
A1	-	RELEASE NUMBER	13MAR20	BROOK	TOMMY			





		<b>↓</b>
17.9±1.0		Ø9.6±1.0
<u> </u>	(65.8)	1
-	(03.6)	

PART NUMBER CHART			
COLOR	PART NUMBER		
GREY	ATM2S-BT		
BLACK	ATM2S-BT-BK		
YELLOW	ATM2S-BT-YW		

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. THIS PART IS USED ON ATM06-2S PLUG WITH ANY MODIFICTION THAT DOES NOT INCLUDE AN END CAP.
- 2. TEMPERATURE RATING : -29°C TO +100°C [-20°F TO +212°F]
- 3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	SEE PART NUMBER CHART			REF: DTM2S	-BT , DTM2S-BT-BK , DTM	12S-BT-YW		
	PART NUMBER				DE	SCRIPTION		ITEM
QUANTITY		ı	MAT	ERI	ALS LI	ST		
	UNLESS OTHERWISE SPECIFIED		IATURES	DATE	Λ	mnha	nal	
1) All dimensions are in metric(mm). 2) Tolerances are as follows:  1 PL DEC ±0.30   Fractions ±1/64		DRAWN:	BROOK.DING	13MAR20	Amphenol			
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION.LI	16MAR20	Sine Systems - www.amphenol-sine.com			
3) Note reference = X		ENGINEER:			44724 Morley Drive			
MATERIAL SPECIFICA	MATERIAL SPECIFICATIONS:		TOMMY.XIE	17MAR20		Clinton Township, MI 480	130	
P\	/C	CUSTOMER:		ВО		BOOT, ATM, 2 WAY,PLUG		
PROCESS SPECIFICATIONS:  NEXT ASSY:		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA						
		SHOWN HERE THE AMPHEN OF REPRODU	ONS AND PERFO EON ARE THE PF OL CORPORATIO CTION ARE IMPL ARE SUBJECT T	ROPERTY OF ON. NO RIGHTS LIED. ALL	A C-	ATM2S-B	T-XX	A1
			RING VARIATION	S.	SCALE: NONE		SHEET 1	DF 1