



TITLE: BOOT, ATM, 3 WAY, PLUG	DWG NO:	ATM3S-BT-XX	REV:A1	SH: 1	OF: 1	
-------------------------------	---------	-------------	--------	-------	-------	--









PART NUMBER CHART					
COLOR	PART NUMBER				
GREY	ATM3S-BT				
BLACK	ATM3S-BT-BK				
YELLOW	ATM3S-BT-YW				

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. THIS PART IS USED ON ATM06-3S PLUG WITH ANY MODIFICTION THAT DOES NOT INCLUDE AN END CAP.
- 2. TEMPERATURE RATING : -29°C TO +100°C [-20°F TO +212°F]
- 3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	SEE PART NUMBER CHART			REF:DTM	REF:DTM3S-BT,DTM3S-BT-BK,DTM3S-BT-YW				
	PART N	ART NUMBER			DESCRIPTION			ITEM	
QUANTITY MATERIALS LIST									
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64		SIGN	ATURES	DATE	DATE Amphono		I		
		DRAWN:	BROOK.DING	13MAR20	Amphenol				
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION.LI	16MAR20	Sine Systems - www.amphenol-sine.com				
3) Note reference	- X	ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY.XIE	17MAR20					
PVC CUSTOMER:			BOOT, ATM, 3 WAY, PLUG						
PROCESS SPECIFICATIONS: PROCESS SPECIFICATIONS: PROCESS SPECIFICATIONS: PROCESS SPECIFICATIONS: PROCESS SPECIFICATIONS: SPECIFICATIONS AND PERFORMANCE E SHOWN HEREON ARE THE PROPERTY C THE AMPIENOL CORPORATION. NO RIG OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		FEATURES, DRMANCE DATA ROPERTY OF	SIZE TYPE	DWG NO:	T VV	REVISION			
		ICTION ARE IMP ARE SUBJECT T	LIED. ALL	A G-	ATM3S-B	SHEET 1	A1		