


| REVISIONS | | | | | | |
|-----------|-----|-----------------|-----------|-------|-------|--|
| REV | ECO | DESCRIPTION | DATE | BY | APPR | |
| A1 | - | RELEASE DRAWING | 24/AUG/19 | PETER | TOMMY | |



REQUIRES CONTACT RETENTION WEDGE AWP-6S



30.0





TITLE

PLUG, 6 SOCKET, ATP SERIES

DWG NO:

ATP06-6S-XXX

REV: A1 SH:

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: N/A


3. SPECIFICATIONS:

- 3.1 CURRENT RATING: 25 AMPS
 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP04-6P* RECEPTACLE. (* = MODIFICATIONS AND COLORS)

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

| CONTACT | MIN. INSUL | MAX. INSUL | TYPICAL |
|---------|----------------------|----------------------|------------|
| SIZE | O.D. | O.D. | WIRE RANGE |
| 12 | 3.40 mm (.134 in) | 4.95 mm (.195 in) | |



| PART NUMBER CHART | | | | |
|-------------------|--------------|--|--|--|
| COLOR | PART NUMBER | | | |
| GREY | ATP06-6S | | | |
| BLACK | ATP06-6S-BLK | | | |

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

| | | | | | | | | | | <u> </u> |
|--|----------------------------|--------------------------------------|---|--|--|------|--------------------------|------------|------|----------|
| | SEE PART NUMBER CHART | | | | | | | | | 9 |
| | PART NUMBER | | | | | DE | SCRIPTION | | ITEM | 1- |
| QUANTITY | MA | | | ERI | λLS | S LI | ST | | | \vdash |
| | UNLESS OTHERWISE SPECIFIED | | NATURES | | | | nol | | 1 | |
| All dimensions are in metric(mm). Tolerances are as follows: PL DEC ±0.30 Fractions ±1/64 | | DRAWN: | PETER.YANG | 24/AUG/19 | | | | | | |
| 2 PL DEC ±0.15 3 PL DEC ±0.08 | 2 PL DEC ±0.15 Angles ±1° | | ORION.LI | 24/AUG/19 | Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036 | | | | | |
| 3) Note reference = X | | ENGINEER: | | | | | | | | |
| MATERIAL SPECIFICA | MATERIAL SPECIFICATIONS: | | TOMMY.XIE | 24/AUG/19 | | | Clinton Township, WI 460 | 550 | | + |
| PROCESS SPECIFICATIONS: | | CUSTOMER: | | PLUG. 6 SOCKET.ATP SERIES | | | | | | |
| | | THIS DRAWING IS SUPPLIED FOR | | | | | | | | |
| | | SHOWN HER THE AMPHEN OF REPROD | ONS AND PERFO EON ARE THE PR NOL CORPORATION UCTION ARE IMPL | ROPERTY OF ON. NO RIGHTS LIED. ALL | В | C- | ATP06-6S | -XXX | A1 | |
| | | | RING VARIATION | IS. | SCALE: N | IONE | | SHEET 1 OF | 1 |] |
| | | | | | | | | | | |

ATP Series™ - Contact Size 12 Options

| Machined Contacts, Sockets & Pins | | | | | |
|--|--|----------|-------|----------|--|
| Part Number | Description | Size | AWG | Туре | |
| AT60-204-12141-10 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Machined | |
| AT62-203-12141-10 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Machined | |
| AT60-220-1231 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Machined | |
| AT62-210-1231 Female Contact - Socket, Gold-plated 12 12-14 Ma | | Machined | | | |
| AT60-204-12141 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Machined | |
| AT62-203-12141 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Machined | |

| Stamped & Formed Contacts, Sockets & Pins | | | | | | |
|--|--|------|-------|------------------|--|--|
| Part Number | Description | Size | AWG | Туре | | |
| AT60-12-0244 | Male Contact - Pin, Gold-plated | 12 | 10-12 | Stamped & Formed | | |
| AT62-12-0244 | Female Contact - Socket, Gold-plated | 12 | 10-12 | Stamped & Formed | | |
| AT60-12-0222 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Stamped & Formed | | |
| AT62-12-0222 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Stamped & Formed | | |
| AT60-12-0144 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Stamped & Formed | | |
| AT62-12-0144 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Stamped & Formed | | |
| AT60-12-0166 Male Contact - Pin, Nickel-plated | | 12 | 12-14 | Stamped & Formed | | |
| AT62-12-0166 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Stamped & Formed | | |

| Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective | | | | | | |
|--|--|----|-----|----------|--|--|
| Part Number Description S | | | AWG | Туре | | |
| 65-54749 Male Contact - DiagnosticGrade™, Pin, Gold-plated | | 12 | 20 | Machined | | |
| AT62-210-1231-1820 Female Contact - DiagnosticGrade™, Socket, Gold-plated | | 12 | 20 | Machined | | |

DiagnosticGrade™ Machined Contacts, Sockets & Pins

| Tooling - Machined Contacts | | | | |
|-----------------------------|-------------|--|--|--|
| Part | Part Number | Description | | |
| | CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only) | | |
| SP F | CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only) | | |

| | Contact Removal Tools | | | | |
|------------|-------------------------|---|--|--|--|
| Part | Part Number Description | | | | |
| - Comments | ATRT-100 | Used for removal of contacts for A Series™ products | | | |
| | AT11-337-1205 | Contact Removal Tool, Plastic, Size 12 | | | |
| | A114017 | Sealing Plug, Size 12, White | | | |

| Tooling - Stamped & Formed Contacts | | | | | |
|-------------------------------------|-------------|---|--|--|--|
| Part | Part Number | Description | | | |
| | MFX-3973 | Crimp Die - Size 12 (S&F contacts only) | | | |
| | MFX-3985 | Crimp Die - Size 12 (S&F contacts only) 10-12AWG -02XX Series | | | |
| | ATT-12-00 | Hand Crimp Tool - Size 12, 12AWG (S&F contacts only) | | | |
| | ATT-12-01 | Hand Crimp Tool - Size 12, 10AWG (S&F contacts only) | | | |

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 01/2022