



## ATUM-19/6-0-SP Product Details

[Share](#) | [Print](#) | [Email](#)


ATUM-19/6-0-SP

TE Internal Number: 5067454043

 **Active**

### Heat Shrink Tubing

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Heat Shrinkable Tubing
- Product Name = ATUM
- Product Source = U.K., U.S.
- Semiflexible
- Thin Wall Style

[View all Features](#)

#### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Product Type](#) = Heat Shrinkable Tubing
- Material = Crosslinked Polyolefin
- Color = Black

#### Electrical Characteristics:

- Product Source = U.K., U.S.
- [Expanded ID, Min. \(mm \[in\]\)](#) = 19.00 [0.748]
- [Recovered ID, Max. \(mm \[in\]\)](#) = 6.00 [0.236]
- Product Use = Cable Breakouts, Cable Ends, Connector-to-Cable Transitions, Electronic Components, Harnesses, Wire Breakouts, Wire Splices

#### Body Features:

- [Product Name](#) = ATUM
- Pliancy = Semiflexible
- [Wall Style](#) = Thin
- [Wall Type](#) = Dual
- [Lining Type](#) = Adhesive
- [Shrink Ratio](#) = 3:1
- Fluid Type = Aviation Fuel, Brake Fluid, Chemicals/Solvents, Hydraulic Fluid, Lubricating Oil, Water
- Resistant To = Fluids, Mechanical Damage, Strain
- Wall Thickness - Full Recovery (Nominal) (mm [in]) = 2.25 [0.088]

#### Housing Features:

- Material Systems = No
- Flammability Rating Type = Flame-Retardant

#### Industry Standards:

- Government/Industry Qualification = No
- UL Rating = Recognized
- CSA Certified = No
- Approved Standards = UL E85381
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Environmental:

- Fluid Resistance = Moisture, Splash Protection
- [Operating Temperature \(°C\)](#) = -55 - +110

#### Conditions for Usage:

- Full Recovery Temperature (°C) = 110
- Shrink Temperature, Min. (°C) = 80
- High Temperature Compatible = No

#### Operation/Application:

- Application = Cable Jacket Repair Sleeve, Cable Jacketing, Insulation and Protection, Sealing
- Emission Free = No

#### Packaging Features:

- Packaging Method = Spool

#### Other:

- Brand = Raychem

#### Corporate Information

[About TE](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)

#### Quick Links

[Check Distributor Inventory](#)  
[Cross Reference Products](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

#### Customer Support

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage Your Account](#)

#### Keep Me Informed

Receive TE News, Events & Technology Updates



