

AZ697

10 AMP MINIATURE POWER RELAY

FEATURES

- Dielectric strength 5000 Vrms
- Low cost
- Epoxy sealed version available
- 10 Amp switching — single pole contacts
- UL TV-5
- Isolation spacing greater than 8mm
- UL Class B insulation system, Class F available
- UL, CUR file E44211; TÜV file R50129288



CONTACTS

Arrangement	SPST (1 Form A) SPDT (1 Form C)
Ratings	Resistive load: Max. switched power: 300 W or 2770 VA Max. switched current: 10 A Max. switched voltage: 150* VDC or 380 VAC *Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Rated Load UL, CUR	TV-5 at 120 VAC [1][2][3] 10 A at 277 VAC, General Use [1] 10 A 30 VDC, Resistive [1] 1/3 HP at 250 VAC [1] 1/4 HP at 125 VAC N.O. [1] 10 A at 277 VAC, General Use, 100k cycles [2][3] 10 A at 30 VDC, Resistive, 100k cycles [2][3] 1/3 HP at 250 VAC, 100k cycles [2][3] 1/4 HP at 125 VAC, 100k cycles [2][3]
TÜV	10 A at 250 VAC, 30 VDC Resistive 100k cycles [1][2] 10 A at 250 VAC, 30 VDC Resistive 50k cycles [3]
Material	Silver cadmium oxide [1], silver nickel [2], silver tin oxide [3], Gold plating available
Resistance	< 50 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power At Pickup Voltage (typical)	257 mW
Max. Continuous Dissipation Temperature Rise	1.9 W at 20°C (68°F) ambient (Class B) 2.5 W at 20°C (68°F) ambient (Class F) 34° C (61°F) at nominal voltage
Temperature	Max. 130°C (266°F) Class B Max. 155° C (311° F) Class F

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ 1 x 10 ⁵ at 10 A 240 VAC Res.
Operate Time (typical)	8 ms at nominal coil voltage
Release Time (typical)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	5000 Vrms coil to contact 1000 Vrms between open contacts
Insulation Resistance	1000 megohms min. at 20°C, 500 VDC 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 90°C (194°F) Class B -40°C (-40°F) to 110°C (230°F) Class F -40°C (-40°F) to 130°C (266°F) Class B -40°C (-40°F) to 155°C (311°F) Class F
Vibration	0.062" DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	18 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

4/9/09W

AZ697

RELAY ORDERING DATA

COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance	Form A (SPST)	Form C (SPDT)
3	2.1	5.7	17 ±10%	AZ697-1A-3D	AZ697-1C-3D
5	3.5	9.4	47 ±10%	AZ697-1A-5D	AZ697-1C-5D
6	4.2	11.4	68 ±10%	AZ697-1A-6D	AZ697-1C-6D
9	6.3	17.4	160 ±10%	AZ697-1A-9D	AZ697-1C-9D
12	8.4	22.8	275 ±10%	AZ697-1A-12D	AZ697-1C-12D
18	12.6	27.9	650 ±10%	AZ697-1A-18D	AZ697-1C-18D
24	16.8	45.7	1100 ±15%	AZ697-1A-24D	AZ697-1C-24D
48	33.6	89.0	4170 ±15%	AZ697-1A-48D	AZ697-1C-48D
60	42.0	115.3	7000 ±15%	AZ697-1A-60D	AZ697-1C-60D
110	79.3	170.5	22900 ±15%	AZ697-1A-110D	AZ697-1C-110D

*For silver nickel contacts change "-1A" or "-1C" to "-1AB" or "-1CB". For silver tin oxide contacts change "-1A" or "-1C" to "-1AE" or "-1CE". For epoxy seal change "D" to "DE". For gold plating change "D" or "DE" to "DA" or "DEA". For Class F insulation add suffix "F" to part number.

HARDWARE ORDERING DATA

DESCRIPTION	ORDER NUMBER	DESCRIPTION	ORDER NUMBER
Socket	ST482-U1	Retainer	ST482-2

MECHANICAL DATA

Form A and C

Terminal No.	Dimensions Tol.: ± 0.005 (0.13)
1,2,3,5	0.018 (0.457) x 0.038 (0.965)
4	0.011 (0.279) x 0.038 (0.965)

PC BOARD LAYOUT

Viewed toward terminals

WIRING DIAGRAM

Form A

Form C

Viewed toward terminals

ST482-U1 HARDWARE

ST482-2 HARDWARE

RETAINING CLIP

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± .010"



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM