

# Brady B-7425 Workhorse® Series Thermal Transfer Labels



As part of Brady's Workhorse Label Series, the B-7425 thermal transfer labels are engineered to withstand the harshest environments across a wide variety of laboratory applications. These labels are constructed with durable polypropylene material to provide a tough and economical solution for improved identification and workflow tracking in the lab. They're ideal for a broad range of processes and applications, including samples, inventory, general tracking, and identification of vials, tubes, racks, flasks, bags and other sample containers.

## Key features:

- Economical solution for vials and tubes from 0.5ml to 50ml
- Use on tubes, vials, boxes, racks, slides, microplates, flasks, dishes, bags or other general needs
- Apply to dry room temperature samples with no overlap needed
- Adhere to stainless steel, glass and polypropylene
- Withstand temperature ranges from -196°C to 121°C (-320°F to 248°F)
- Use in LN2, freezers, autoclave, and hot water baths.
- Chemical resistance to ethanol, DMSO, IPS, short term xylene, 10% formalin, 50% acetic acid and toluene
- Prints best with R6400 black ribbon (can also use R4300 or R6200 black ribbon)
- Stock sizes available for Brady portable and benchtop thermal transfer printers, as well as 1" and 3" core rolls for other industry printers
- Custom label sizes and print automation options available
- -AC indicates steam sterilization with a color changing pre-printed header when autoclaved at 250.7° F (121.5° C) for 10 minutes

**For more information, call a Brady Lab Specialist at 1-800-356-9951, contact your lab distributor or visit [BradyID.com/lab](http://BradyID.com/lab)**

Diagram	Catalog #	Material	Color	Label Width Inch (mm)	Label Height Inch (mm)	Label Area C Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
<b>IP Printer, PR+ Printers</b>									
Fig. 29	THT-257-7425-2	B-7425	White	0.825 (21.0)	0.250 (6.4)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-152-7425-2	B-7425	White	1.000 (25.4)	0.375 (9.5)	-	2	2000	IP-R4302, R4302
Fig. 24	THT-249-7425-2	B-7425	White	1.000 (25.4)	0.375 (9.5)	0.375 (9.5) dia.	1	2000 sets	IP-R4302, R4302
Fig. 29	THT-59-7425-2	B-7425	White	1.000 (25.4)	0.500 (12.7)	-	1	2000	IP-R4302, R4302
Fig. 24	THT-251-7425-2	B-7425	White	1.000 (25.4)	0.500 (12.7)	0.440 (11.1) dia.	1	2000 sets	IP-R4302, R4302
Fig. 29	THT-88-7425-2	B-7425	White	1.000 (25.4)	0.750 (19.1)	-	2	2000	IP-R4302, R4302
Fig. 29	THT-179-7425-2	B-7425	White	1.000 (25.4)	1.000 (25.4)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-256-7425-2	B-7425	White	1.300 (33.0)	0.600 (15.2)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-37-7425-2	B-7425	White	1.500 (38.1)	0.500 (12.7)	-	2	2000	IP-R4307, R4307
Fig. 29	THT-136-7425-2	B-7425	White	1.500 (38.1)	0.750 (19.1)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-235-7425-2	B-7425	White	1.500 (38.1)	1.000 (25.4)	-	1	2000	IP-R4302, R4302
Fig. 29a	THT-235-7425-2-AC	B-7425-AC	White	1.500 (38.1)	1.000 (25.4)	-	1	2000	R4300
Fig. 29	THT-258-7425-2	B-7425	White	1.500 (38.1)	1.750 (44.5)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-151-7425-2	B-7425	White	2.000 (50.8)	0.250 (6.4)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-53-7425-2	B-7425	White	2.000 (50.8)	0.500 (12.7)	-	1	2000	IP-R4302, R4302
Fig. 29	THT-137-7425-2	B-7425	White	2.000 (50.8)	1.000 (25.4)	-	1	2000	IP-R4302, R4302
Fig. 29a	THT-137-7425-2-AC	B-7425-AC	White	2.000 (50.8)	1.000 (25.4)	-	1	2000	R4300
<b>BBP12 Printer</b>									
Fig. 29	THT-257-7425-2-SC	B-7425	White	0.825 (21.0)	0.250 (6.4)	-	1	2000	R4313
Fig. 29	THT-152-7425-2-SC	B-7425	White	1.000 (25.4)	0.375 (9.5)	-	2	2000	R4313
Fig. 24	THT-249-7425-2-SC	B-7425	White	1.000 (25.4)	0.375 (9.5)	0.375 (9.5) dia.	1	2000 sets	R4313
Fig. 29	THT-59-7425-2-SC	B-7425	White	1.000 (25.4)	0.500 (12.7)	-	1	2000	R4313
Fig. 24	THT-251-7425-2-SC	B-7425	White	1.000 (25.4)	0.500 (12.7)	0.440 (11.1) dia.	1	2000 sets	R4313
Fig. 29	THT-88-7425-2-SC	B-7425	White	1.000 (25.4)	0.750 (19.1)	-	2	2000	R4313
Fig. 29	THT-179-7425-2-SC	B-7425	White	1.000 (25.4)	1.000 (25.4)	-	1	2000	R4313
Fig. 29	THT-256-7425-2-SC	B-7425	White	1.300 (33.0)	0.600 (15.2)	-	1	2000	R4313
Fig. 29	THT-37-7425-2-SC	B-7425	White	1.500 (38.1)	0.500 (12.7)	-	2	2000	R4313
Fig. 29	THT-136-7425-2-SC	B-7425	White	1.500 (38.1)	0.750 (19.1)	-	1	2000	R4313
Fig. 29	THT-235-7425-2-SC	B-7425	White	1.500 (38.1)	1.000 (25.4)	-	1	2000	R4313
Fig. 29	THT-258-7425-2-SC	B-7425	White	1.500 (38.1)	1.750 (44.5)	-	1	2000	R4313
Fig. 29	THT-151-7425-2-SC	B-7425	White	2.000 (50.8)	0.250 (6.4)	-	1	2000	R4313
Fig. 29	THT-53-7425-2-SC	B-7425	White	2.000 (50.8)	0.500 (12.7)	-	1	2000	R4313
Fig. 29	THT-137-7425-2-SC	B-7425	White	2.000 (50.8)	1.000 (25.4)	-	1	2000	R4313
<b>BBP33 Printer</b>									
Fig. 29	B33-257-7425	B-7425	White	0.825 (21.0)	0.250 (6.4)	-	1	1500	B30-R4300
Fig. 29	B33-152-7425	B-7425	White	1.000 (25.4)	0.375 (9.5)	-	2	2000	B30-R4300
Fig. 24	B33-249-7425	B-7425	White	1.000 (25.4)	0.375 (9.5)	0.375 (9.5) dia.	1	1500	B30-R4300
Fig. 29	B33-59-7425	B-7425	White	1.000 (25.4)	0.500 (12.7)	-	1	2000	B30-R4300
Fig. 24	B33-251-7425	B-7425	White	1.000 (25.4)	0.500 (12.7)	0.440 (11.1) dia.	1	1500	B30-R4300
Fig. 29	B33-88-7425	B-7425	White	1.000 (25.4)	0.750 (19.1)	-	2	2000	B30-R4300
Fig. 29	B33-179-7425	B-7425	White	1.000 (25.4)	1.000 (25.4)	-	1	1500	B30-R4300
Fig. 29	B33-256-7425	B-7425	White	1.300 (33.0)	0.600 (15.2)	-	1	1500	B30-R4300
Fig. 29	B33-37-7425	B-7425	White	1.500 (38.1)	0.500 (12.7)	-	2	1500	B30-R4300
Fig. 29	B33-136-7425	B-7425	White	1.500 (38.1)	0.750 (19.1)	-	1	1500	B30-R4300
Fig. 29	B33-235-7425	B-7425	White	1.500 (38.1)	1.000 (25.4)	-	1	1250	B30-R4300
Fig. 29a	B33-235-7425-AC	B-7425-AC	White	1.500 (38.1)	1.000 (25.4)	-	1	1250	B30-R4300
Fig. 29	B33-258-7425	B-7425	White	1.500 (38.1)	1.750 (44.5)	-	1	900	B30-R4300
Fig. 29	B33-151-7425	B-7425	White	2.000 (50.8)	0.250 (6.4)	-	1	2000	B30-R4300
Fig. 29	B33-53-7425	B-7425	White	2.000 (50.8)	0.500 (12.7)	-	1	2000	B30-R4300
Fig. 29	B33-137-7425	B-7425	White	2.000 (50.8)	1.000 (25.4)	-	1	1500	B30-R4300
Fig. 29a	B33-137-7425-AC	B-7425-AC	White	2.000 (50.8)	1.000 (25.4)	-	1	1500	B30-R4300
<b>BMP21-PLUS, BMP21-LAB Printers</b>									
Fig. 33	M21-375-7425	B-7425	BK on WT	0.375 (9.5)	21 ft (6.4 m)	-	1 roll (cont.)	-	-
Fig. 33	M21-500-7425	B-7425	BK on WT	0.500 (12.7)	21 ft (6.4 m)	-	1 roll (cont.)	-	-
Fig. 33	M21-750-7425	B-7425	BK on WT	0.750 (19.1)	21 ft (6.4 m)	-	1 roll (cont.)	-	-




Figure 24




Figure 29




Figure 29a




Figure 33

▶ **For more information, call a Brady Lab Specialist at 1-800-356-9951, contact your lab distributor or visit BradyID.com**

USA  
Customer Service: 1-888-272-3946  
Inside Sales: 1-888-311-0775  
BradyID.com

Canada  
Customer Service: 1-800-263-6179  
BradyCanada.ca

Mexico  
Customer Service: 1-800-262-7777  
Inside Sales: 1-800-262-7777 ext 177  
BradyLatinAmerica.com

