

Heavy-Duty Battery Connectors

Abrasion resistant and engineered for optimum performance at both high and low temperatures.

Blackburn® Battery/Starter Cables

- Fine flexible copper rope stranding PVC jacket conforms to SAE J1127 specifications
- Layer of paper separates insulation from copper, providing easy stripping with no stranding damage
- Temperature rated for 80° C
- Flexibility ideal for tight spaces and cold environments
- Blackburn® Color-Keyed® system markings for fast and accurate identification
- Marked in 1-ft. increments for easy measurement
- Available in red or black jacket color

CAT. NO.	SAE CABLE SIZE	CABLE LENGTH	CABLE COLOR
BC4-100	4 Gauge	100 ft.	BLACK
BC2-100	2 Gauge	100 ft.	
BC1-100	1 Gauge	100 ft.	
BC10-100	1/0 Gauge	100 ft.	
BC20-100	2/0 Gauge	100 ft.	
BC30-100	3/0 Gauge	100 ft.	
BC40-100	4/0 Gauge	100 ft.	
BC4-1000	4 Gauge	1000 ft.	
BC2-500	2 Gauge	500 ft.	
BC1-500	1 Gauge	500 ft.	
BC10-500	1/0 Gauge	500 ft.	
BC20-500	2/0 Gauge	500 ft.	
BC30-500	3/0 Gauge	500 ft.	
BC40-500	4/0 Gauge	500 ft.	
BC4-500R	4 Gauge	500 ft.	RED
BC2-500R	2 Gauge	500 ft.	
BC1-500R	1 Gauge	500 ft.	
BC10-500R	1/0 Gauge	500 ft.	
BC20-500R	2/0 Gauge	500 ft.	
BC30-500R	3/0 Gauge	500 ft.	
BC40-500R	4/0 Gauge	500 ft.	

CAT. NO.	SAE CABLE SIZE	CABLE LENGTH	CABLE COLOR
BC4-25	4 Gauge	25 ft.	BLACK
BC2-25	2 Gauge	25 ft.	
BC1-25	1 Gauge	25 ft.	
BC10-25	1/0 Gauge	25 ft.	
BC20-25	2/0 Gauge	25 ft.	
BC30-25	3/0 Gauge	25 ft.	
BC40-25	4/0 Gauge	25 ft.	
BC4-25R	4 Gauge	25 ft.	
BC2-25R	2 Gauge	25 ft.	
BC1-25R	1 Gauge	25 ft.	
BC10-25R	1/0 Gauge	25 ft.	
BC20-25R	2/0 Gauge	25 ft.	
BC30-25R	3/0 Gauge	25 ft.	
BC40-25R	4/0 Gauge	25 ft.	



Material: High-Conductivity Copper

Finish: Electro-Tin Plate

Installing Tools: TBM5-SV or TBM5V



Connectors & Grounding — Blackburn® Compression Connectors Featuring the Color-Keyed® System

Specially designed for demanding industrial and OEM requirements.

Heavy-Duty Battery Cable

- 105° C temperature rated and UL® recognized
- Heavier PVC jacket conforms to SAE J1127 specifications
- Blackburn® Color-Keyed® system markings for fast and accurate identification
- Marked in 1-ft. increments for easy measurement
- Layer of paper separates insulation from copper for easy stripping with no strand damage
- 600V rated available in bulk only
- Application specific — call to order

