



**Location:** United States

**PRO Industrial Controls**

N53 W24794 S Corporate Circle

## Flexible Conduits & Fittings

**T&B Catalog Number:**

BFVL-121010

**UPC Number:**

78620994572

**Status:**

Active

**Description:**

PMAFIX one-piece black 'V' connector, material - polyamide 6, conduit size - 12, 10, 10.

### Application

For cable protection systems in a wide range of applications

### Characteristics

- Extremely high impact resistance
- Vibration-proof connection to PMAFLEX conduits
- Easy mounting
- High conduit pull-out strength
- Very good chemical properties
- Free from halogens and cadmium
- Fits both conduit profiles - fine (T) and coarse (G)

### General

Material	Polyamide 6
Color	Black
Suitable for Use With	PMAFLEX, PMA Smart Line

### Dimension Information

Fits to Conduit Size (NW)	12
Fits to Conduit Size (metric)	16
Fits to Conduit Size (inches)	3/8
Output fits to conduit size NW	10
Output fits to conduit size - Metric	12

### Technical Information

Temperature Range-Continuous (Celsius)	-40 degree C - +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

### Specifications

3dmodel	Available on Website
---------	----------------------

### IP Ratings

IP Rating	IP67 stat. / IP65 dyn.
-----------	------------------------

### Packaging

T&B Inner Pack	20
Package in Units	200
T&B Sold in UOM	Each
T&B Weight Per UOM	0.01 lbs. Each

## Application Support

PMA Reference Guide	Available on Website
Product Overview-PMAFIX Connectors	Available on Website
PMAFIX Connectors-Safety and Sealing Systems	Available on Website

## Certifications

RoHS Compliance	Yes
-----------------	-----

## Certifications



### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: techsupport@tnb.com