Note: This datasheet may be out of date

Please download the latest datasheet of BLF02GD162GNE# from the official website of Murata Manufacturing

https://www.murata.com/en-us/products/productdetail?partno=BLF02GD162GNE%23

BLF02GD162GNE#

"#" indicates a package specification code.








< List of part numbers with package codes > BLF02GD162GNED BLF02GD162GNEB



Appearance & Shape







- 1. Frequency specified filters are designed to reduce noise greatly at specified frequency. which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLF series is effective in circuits without stable ground lines because BLF series does not need a connection to ground.
- 2. The nickel barrier structure of the external electrodes provides excellent solder heat resistance.
- 3.BLF02GD series is designed to have high impedance especially, at 700MHz to 1GHz. Suitable for immunity noise suppression for GSM band.



Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
D	180mm Paper Tape	15000
В	Bulk(Bag)	1000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/08/08



 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLF02GD162GNE\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=BLF02GD162GNE%23

BLF02GD162GNE#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD	
Size Code (in mm)	0402	
Size Code (in inch)	01005	
Length	0.4mm	
Length Tolerance	±0.02mm	
Width	0.2mm	
Width Tolerance	±0.02mm	
Thickness	0.3mm	
Thickness Tolerance	±0.02mm	
Impedance (at Target Frequency)	1600Ω±40% (at 700MHz)	
Rated Current (at 85°C)	100mA	
Rated Current (at 125°C)	100mA	
DC Resistance(max.)	3Ω	
Operating Temperature Range	-55°C to 125°C	
Mass(typ.)	0.125mg	
Number of Circuit	1	

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/08/08


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-us/products/productdetail?partno=BLF02GD162GNE\%23} \\$

BLF02GD162GNE#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/08/08