

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of BLM18DN151SZ1# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=BLM18DN151SZ1%23

BLM18DN151SZ1#


"#" indicates a package specification code.


In Production RoHS REACH AEC-

< List of part numbers with package codes > BLM18DN151SZ1D BLM18DN151SZ1J BLM18DN151SZ1B

0.4±0.2

1.6±0.15





Chip ferrite beads for high frequency noise suppression over a wide frequency range.

Features

0.8±0.

Electrode

0.8±0.15

- 1. High impedance characteristic in 1GHz or higher frequency
- 2. High impedance characteristic over a wide frequency band range of 100MHz to 6GHz
- 3. Low DC Resistance enables large Rated Current



Automotive Usage

Packaging Information

Packaging	Specifications	Minimum Order Quantity
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000
В	Bulk(Bag)	1000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

Please download the latest datasheet of BLM18DN151SZ1# from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM18DN151SZ1%23

BLM18DN151SZ1#

"#" indicates a package specification code.

Specifications

Shape	SMD	Mass(typ.)	0.004g
Size Code (in mm)	1608	Number of Circuit	1
Size Code (in inch)	0603		"
Length	1.6mm		
Length Tolerance	±0.15mm		
Width	0.8mm		
Width Tolerance	±0.15mm		
Thickness	0.8mm		
Thickness Tolerance	±0.15mm		
Impedance (at 100MHz)	150Ω		
Impedance (at 100MHz) Tolerance	±25%		
Impedance (at 1GHz)	400Ω		
Impedance (at 1GHz) Tolerance	±30%		
Rated Current (at 85°C)	1.4A		
Rated Current (at 125°C)	900mA		
DC Resistance(max.)	0.12Ω		
Operating Temperature Range	-55℃ to 125℃		

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

2 of 3

Note: This datasheet may be out of date.

Please download the latest datasheet of BLM18DN151SZ1# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-eu/products/productdetail?partno=BLM18DN151SZ1%23

BLM18DN151SZ1#

"#" indicates a package specification code.

Product Data


INNOVATOR IN FLECT



In operating temperature exceeding +85°C, derating of current is necessary for this series.

Please apply the derating curve shown in chart according to the operating temperature.

Derating of Rated Current



Impedance-Frequency Characteristics

Derating of Rated Current

(Resistance element becomes dominant at high frequencies.)

Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

