

BP24V33 - External Battery Pack for UPS System

MODEL NUMBER: BP24V33





Description

Tripp Lite's BP24V33 external battery pack offers extended battery runtime when used in conjunction with Tripp Lite SmartPro UPS systems with a 24VDC external battery connection. Stackable form factor supports configuration with up to 2 battery packs stacked with the UPS on top. Rugged all metal battery enclosure safely houses UPS batteries and includes heavy gauge cabling with pre-installed DC connectors for simple installation. Additional output connector allows multiple BP24V33 battery packs to be daisy-chained to the UPS for even longer extended run operation.

Features

- Offers extended-run UPS operation when used in conjunction with Tripp Lite UPS systems with a 24V DC external battery connection
- Supports stacking installation of two battery packs with the UPS on top
- Includes input and output connectors to support the connection of multiple battery packs for even longer extended run operation
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

Highlights

- Extends runtime of Tripp Lite
 UPS Systems with 24V DC
 external battery connection
- Provides daisy-chain capability
- Simple installation; stackable
- 2 year warranty

Applications

• BP24V33 external battery pack is ideal for lengthening the battery runtime provided by Tripp Lite UPS systems equipped with a 24V DC external battery connection. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired. **COMPATIBLE WITH** SMART2200NET, SMART2200XLNET, SMART3000NET, SMART2200RMXL. SMARTINT3000. SMARTINT3000RM and other Tripp Lite UPS systems specifying the use of this pack.

Package Includes

- BP24V33 external battery pack
- Warranty information
- Instruction manual

BATTERY	
Expandable Battery Runtime	Red female DC connector for additional battery packs
DC System Voltage (VDC)	24
UPS Connection	3 ft. attached cable with red DC connector
Typical Battery Lifespan	4-6 years typical (North America)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PHYSICAL		
Shipping Weight (lbs.)	66	
Shipping Weight (kg)	29.94	
Unit Dimensions (hwd / in.)	8 x 11.5 x 13	
Unit Dimensions (hwd / cm)	20.32 x 29.21 x 33.02	
Material of Construction	Putty color steel housing	
Form Factors Supported	Floorstanding tower format. Stackable	
CERTIFICATIONS		
Certifications	Tested to UL, cUL, CE, NOM	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.