

3 and 4-Pin *minifast*® Field Wireable Connectors

- Straight Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection



| Drawing   | Part Number    | Specs  | Application  | Pinout |
|---|----------------|--|--|--------|
| <p>BS 41 ..</p> <p>Ø1.065 [27.0]</p> <p>3.465 [88.0] APPROX</p> <p>7/8-16UN</p> | BS 4131-0/9    | Glass filled nylon<br>PG 9 cable gland,<br>accepts 6-8 mm cable diameter<br>Screw terminals,<br>accepts up to 16 AWG conductors<br>85° C<br>250 V, 12 A      | <i>Mates with all 3-pin<br/>cordsets and<br/>receptacles</i> |        |
|   | BS 4131-0/13.5 | Glass filled nylon<br>PG 13.5 cable gland,<br>accepts 10-12 mm cable diameter<br>Screw terminals,<br>accepts up to 16 AWG conductors<br>85° C<br>250 V, 12 A | <i>Mates with all 3-pin<br/>cordsets and<br/>receptacles</i> |        |
|   | BS 4141-0/9    | Glass filled nylon<br>PG 9 cable gland,<br>accepts 6-8 mm cable diameter<br>Screw terminals,<br>accepts up to 16 AWG conductors<br>85° C<br>250 V, 9 A       | <i>Mates with all 4-pin<br/>cordsets and<br/>receptacles</i> |        |
|   | BS 4141-0/13.5 | Glass filled nylon<br>PG 13.5 cable gland,<br>accepts 10-12 mm cable diameter<br>Screw terminals,<br>accepts up to 16 AWG conductors<br>85° C<br>250 V, 9 A  | <i>Mates with all 4-pin<br/>cordsets and<br/>receptacles</i> |        |

Field Wireables