



[Home](#) / [Products](#) / [Search Result](#)

B-TAP® Insulation-Piercing Tap Connectors

Products

- [Wire Termination](#)
- [Test & Measurement](#)
- [DataComm](#)
- [Tools & Totes](#)
- [Wire Management](#)
- [Wire Installation](#)
- [Mil-Aero Wire Processing](#)
- [OEM Connection Systems](#)
- [Electrical Supplies](#)



Product Resources

 [B-TAP® Insulation-Piercing Tap Connectors MSDS](#)
(PDF | 200K)

Features

- Eliminates split bolts and tape
- Easy two-minute installation requires only box/socket wrench
- Installs on energized systems eliminating costly power shutdowns
- Self-sealing, grease-filled end-cap ensures safe, weather-tight connection
- Unique turbo spacer keeps connector wide open for quick and easy installation
- Torque-regulating nut breaks off when proper tension is reached
- Full-line is 600V dual-rated, 194°F (90°C)

Models	Specifications	
Description		Catalog #
B-TAP® for main cable sizes #1/0 to #8 AWG and tap cable sizes #2 to #10 AWG	BTC1/0-10	
B-TAP® for main cable sizes #2/0 to #4 AWG and tap cable sizes #10 to #14 AWG	BTC2/0-14	
B-TAP® for main cable sizes 250 to #1 AWG and tap cable sizes #3/0 to #4 AWG	BTC250-4	
B-TAP® for main cable sizes 350 to #1/0 AWG and tap cable sizes 350 to #1/0 AWG	BTC350-1/0	
B-TAP® for main cable sizes #4/0 to #3 AWG and tap cable sizes #2 to #10 AWG	BTC4/0-10	
B-TAP® for main cable sizes #4/0 to #2 AWG and tap cable sizes #1/0 to #6 AWG	BTC4/0-6	
B-TAP® for main cable sizes 500 to #4/0 AWG and tap cable sizes 350 to #1/0 AWG	BTC500-1/0	
B-TAP® for main cable sizes 500 to #1/0 AWG and tap cable sizes #10 to #14 AWG	BTC500-14	
B-TAP® for main cable sizes 500 to #2/0 AWG and tap cable sizes #4/0 to #4 AWG	BTC500-4	
B-TAP® for main cable sizes 750 to 250 AWG and tap cable sizes 500 to 250 AWG	BTC750-250	