

**PRODUCT FAMILIES**

- Pin Headers and Sockets
- Clips and Insulators
- Banana Plugs and Jacks
- Grabbers, Probes and Spade Terminals
- Test Leads and Patch Cords
- Coaxial Cable Assemblies
- Coaxial Test Leads**
- Coaxial Break-Outs
- DMM Kits

**Coaxial Test Leads**

**A pioneer and leader in the manufacture of alligator clips, test leads, and banana plugs.**

While the founder of Mueller Electric Company invented alligator clips, the company has since expanded its product lines into electric test clips, test leads, test accessories, and board to board connectors, sold to qualifying manufacturers and through leading authorized distributors. Please browse our various coaxial cable assembly configurations.

**BNC Male to Stackable Double Banana Plug**



Model# BU-5070-B-\*\*-0

- Material: BNC Male Connector: gold-plated center contact, silverplated body; (MIL-C-39012); Double Banana Plug: ABS housing, brass body and beryllium copper, nickel-plated, nine-leaf cage spring; Coaxial Cable: shielded RG58C/U, MIL-C-17F, 50 ohm
- \*\*Length: -12" (.3m), 24" (.6m), 36" (.9m), 48" (1.2m), 60" (1.5m)
- Rating: Hands free testing at 500 VRMS on center conductor

**BNC Male on Both Ends**



Model # BU-5050-B-\*\*-0

- Material: BNC Male Connector: gold-plated center contact, silver-plated body; (MIL-C-39012); Coaxial Cable: shielded RG58C/U, MIL-C17F, 50 ohm
- \*\*Length: -12" (.3m), 24" (.6m), 36" (.9m), 48" (1.2m), 60" (1.5m)
- Rating: Hands free testing at 500 VRMS on center conductor

**BNC Male with Strain Relief on Both Ends**



Model# BU-5454-B-\*\*-0

- Material: BNC Male Connector: MIL-C-39012, silver-plated brass body, gold/nickel plated brass center contact; Coaxial Cable: RG58C/U, MIL-C17F, 50 ohm
- \*\*Length: -12" (.3m), 24" (.6m), 36" (.9m), 48" (1.2m), 60" (1.5m)
- Rating: Hands free testing at 500 VRMS on center conductor

**Insulated BNC Male to BNC Female**



Model# BU-5659-B-\*\*-0

- Material: BNC Male/Female Connector: fully insulated nylon housing; nickel-plated brass body, gold/nickel plated brass center contact; polyethylene dielectric; Coaxial Cable: RG58, 50 ohm
- \*\*Length: -12" (.3m), 24" (.6m), 36" (.9m), 48" (1.2m), 60" (1.5m)
- Rating: Hands free testing at 500 VRMS on center conductor

**TOOL SEARCH TOOLS**

MUELLER OR DISTRIBUTOR STOCK SEARCH

PART #

**SEARCH**

---

**TOOL CROSS COMPETITOR PART #**

Choose a Brand

PART #  **SEARCH**

---

**TOOL MeterMate® DMM ACCESSORY SELECTOR**

Select Meter Make

Select a Make First

---

**TOOL BUILD A PCB HEADER OR SOCKET**

OVER 10,000 IN STOCK! **GO**

**ISO 9001:2000**