



Flexible Conduits & Fittings

T&B Catalog Number:

BVIDA-U180GT

UPC Number:

78620994961

Status:

Active

Description:

PMAFIX black female thread adapter with UNEF threads and universal safety clip. Material - polyamide 6, thread size - 3/4 in. - 20, nominal width/conduit size - 10. For use with AMP connectors.

Application

For cable protection systems in a wide range of applications

Characteristics

Very high impact resistance
 Suitable for the AMP connector series CPC
 Vibration proof connection to PMAFLEX conduits
 High conduit pull-out strength
 Easy installation, simply push the conduit in
 Can be easily re-opened with a screwdriver
 Very good chemical properties
 Free from halogens and cadmium
 Fits both conduit profiles, fine (T) and coarse (G)

General

Material Polyamide 6
 Color Black
 Thread Type UNEF
 Compatible With PMAFLEX, AMP Connector series CPC

Dimension Information

Fits to Conduit Size (NW) 07
 Fits to Conduit Size (metric) 10
 Fits to Conduit Size (inches) 1/4
 Thread Size (UNEF) 3/4" - 20

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C
 Temperature-Short-Term (Celsius) +160 degree C
 Technical Data Sheet Available on Website
 Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP 66 stat. / IP 54 dyn. On conduit side

Packaging

T&B Order Multiple 50
 T&B Inner Pack 50
 Package in Units 700
 T&B Sold in UOM Each
 T&B Weight Per UOM 0.15 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

PMAFIX Connectors-Safety and Sealing Available on Website

Systems

Certifications

RoHS Compliance Yes

Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com