



Flexible Conduits & Fittings

T&B Catalog Number:

BVND-M409GT-10

UPC Number:

78620995120

Status:

Active

Description:

PMAFIX straight black connector with universal safety clip. Material - polyamide 6, thread size M40 x 1.5, conduit size - 29.

Application

For cable protection systems in a wide range of applications

Characteristics

- Very high impact resistance
- Vibration-proof connection to PMAFLEX conduits
- Easy mounting
- High conduit pull-out strength
- Can be easily re-opened with a screwdriver
- Very good chemical properties
- Free from halogens and cadmium
- Fits both conduit profiles - Fine (T) and coarse (G)

General

Material	Polyamide 6
Color	Black
Thread Type	Metric
Suitable for Use With	PMAFLEX, PMA Smart Line

Dimension Information

Fits to Conduit Size (NW)	29
Fits to Conduit Size (metric)	32
Fits to Conduit Size (inches)	1
Thread Size (Metric)	M40 x 1.5

Technical Information

Temperature Range-Continuous (Celsius)	-40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

Specifications

3dmodel	Available on Website
---------	----------------------

IP Ratings

IP Rating	IP 66 stat. / IP 54 dyn.
-----------	--------------------------

Packaging

T&B Order Multiple	900
T&B Inner Pack	30
Package in Units	300
T&B Sold in UOM	Each
T&B Weight Per UOM	0.06 lbs. Each

Application Support

PMA Reference Guide	Available on Website
Product Overview-PMAFIX Connectors	Available on Website

Certifications

RoHS Compliance

Yes

Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com