



Flexible Conduits & Fittings

T&B Catalog Number:

BVNZ-M638S

UPC Number:

78620995279

Status:

Active

Description:

PMAFIX straight black strain relief connector, material - polyamide 6, thread size - M63 x 1.5. conduit size NW - 48, terminal range - 34.0 - 44.0.

Application

For use in machine and plant construction

For separation of damp and dry areas

Characteristics

Very high impact resistance

Vibration proof connection to PMAFLEX conduits

Easy mounting

High conduit pull-out strength

Very good chemical properties

Free from halogens and cadmium

Fits both conduit profiles - Fine (T) and coarse (G)

Integrated strain relief optimally holds and seals cables

If conductors are used with the connector multiple sealing inserts should be considered

General

Material Polyamide 6

Color Black

Thread Type Metric

Compatible With PMAFLEX

Dimension Information

Fits to Conduit Size (NW) 48

Fits to Conduit Size (metric) 50

Fits to Conduit Size (inches) 1 1/2

Thread Size (Metric) M63 x 1.5

Terminal Range 34.0 - 44.0

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

IP Ratings

IP Rating IP68 stat. / IP67 dyn.

Packaging

T&B Order Multiple 10

T&B Inner Pack 10

Package in Units 50

T&B Sold in UOM Each

T&B Weight Per UOM 0.31 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

Available on Website

PMAFIX Connectors-Safety and Sealing
Systems

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com