



## Flexible Conduits & Fittings T&B Catalog Number:

UPC Number: Status: Description: BVWV-M202 78620995385 Active

PMAFIX 90 degree black one-piece universal elbow , material - polyamide 6, conduit size NW - 12, thread size - M20 x 1.5.

Application

	In a wide range of applications where it is important
	that the cable protection system offers a high grade
	of sealing and safety.
Characteristics	
	High pull-out strength values
	Easy installation with the oval clip guarantees an
	excellent connection to PMAFLEX conduits.
	IP rating of up to IP68 can be achieved with the cor-
	responding seals, NVN3 + SVN4.
	Self-extinguishing, free of halogen and cadmium
	and are extremely shock resistant
Osmanal	Fits both conduit profiles - Fine (T) and coarse (G)
General	
Material	Polyamide 6
Color	Black
Thread Type	Metric
Compatiable With	PMAFLEX
Dimension Information	
Fits to Conduit Size (NW)	12
Fits to Conduit Size (metric)	16
Fits to Conduit Size (inches)	3/8
Thread Size (Metric)	M20 x 1.5
Technical Information	
Temperature Range-Continuous (Celsius	$-40$ degree C to $\pm 105$ degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website
Specifications	
-	
3dmodel	Available on Website
IP Ratings	
IP Rating	IP68 stat. / IP67 dyn.
Packaging	
T&B Inner Pack	50
Package in Units	350
T&B Sold in UOM	Each
T&B Weight Per UOM	0.02 lbs. Each
Application Support	
	A 19 11 147 1 15
PMA Reference Guide	Available on Website
Prouduct Overview-PMAFIX Connectors	
	Available on Website



PMAFIX Connectors-Safety and Sealing Systems Certifications

**RoHS** Compliance

Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com